

Dec. 1973

Artesia, NM 88210

UNITED STATES

DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Form Approved.

Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐2. NAME OF OPERATOR
H & S Oil Company ✓3. ADDRESS OF OPERATOR
Suite 303, First Natl. Bank Bldg. - Artesia4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980' FNL 660' FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☐
☒
☒
☐
☒
☐
☐
☐5. LEASE
NM 02931

6. IF INDIAN, ALLOTTEE OR TRIBAL NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Muncy Federal

9. WELL NO.

2

10. FIELD OR WILDCAT NAME

Red Lake Q.G.SA.

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 13-T17S-R27E, NMPM

12. COUNTY OR PARISH

Eddy

13. STATE

NM

14. API NO.

30-015-70256-84

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3510GL

3518 KDB

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

9/17/84 Spudded 2:14 PM- Ran 314 ft. of 8 5/8" Casing. Cemented w/200 sacks class C w/2% Calcium Chloride. Circulated 35 sacks to pit.

9/20/84 Ran 1765' of 5 1/2" casing. Cemented w/262 sacks lite weight and 254 sacks of lite weight 4 with 2% Calcium Chloride.

9/26/84 Perforated from 1486 to 1682 with 12 shots. Acidized and fraced w/1000 gal. HCL acid, 21,000 20/40 sand, 20,000 10/20 sand, 11,000 lbs. 100 mesh sand & 40,000 gals. 30 lb. gel.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Robert R. Spencer TITLE Partner DATE 10/12/84

ACCEPTED FOR RECORD (This space for Federal or State office use)

APPROVED BY GWR TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

OCT 12 1984

C. L. L. L.

NEW MEXICO

*See Instructions on Reverse Side