

NEW MEXICO OIL CONSERVATION COMMISSION  
DRAWER 100  
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Gater Petro Corp.</u>		Lease <u>Powell-Kessinger BS</u>		Well # <u>St 2</u>	
Location of Well	Unit	Section <u>33</u>	Township <u>17</u>	Range <u>25</u>	County <u>Eddy</u>
Drilling Contractor			Type of Equipment <u>Rotary</u>		
<u>APPROVED CASING PROGRAM</u>					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement

Casing Data:

Surface \_\_\_\_\_ joints of \_\_\_\_\_ inch \_\_\_\_\_ # Grade \_\_\_\_\_  
(Approved) (Rejected) \_\_\_\_\_

Inspected by \_\_\_\_\_ date \_\_\_\_\_

Cementing Program

Size of hole 12 1/4" Size of Casing 8 7/8" Sacks cement required \_\_\_\_\_

Type of Shoe used guide Float collar used insert Btm 3 jts welded yes

TD of hole 1122' Set 1120' Feet of 8 7/8" Inch 24 # Grade J-55

New used csg. @ 1120' with 200 22 cc sacks neat cement around shoe  
+ 400 sax Hall's Lite additives (1/4" floreal, 3% occ)

Plug down @ 6845 (AM) (PM) Date 2/12/85

Cement circulated yes No. of Sacks 35 sr

Cemented by Hollister Witnessed by Mike Stubblefield

Temp. Survey ran @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_ top cement @ \_\_\_\_\_

Casing test @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_

Method Used \_\_\_\_\_ Witnessed by \_\_\_\_\_

Checked for shut off @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_

Method used \_\_\_\_\_ Witnessed by \_\_\_\_\_

Remarks: \_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

No centralizers or locaters Last day Break 2 1055'