

STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

Form C-103  
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	<input checked="" type="checkbox"/>
FILE	<input checked="" type="checkbox"/>
U.S.G.S.	
LAND OFFICE	<input checked="" type="checkbox"/>
OPERATOR	<input checked="" type="checkbox"/>

RECEIVED BY  
MAY 31 1985  
O. C. D.  
ARTESIA, OFFICE

5a. Indicate Type of Lease  
State ☒ Fee ☐  
5. State Oil & Gas Lease No.  
LG 3782

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG SALS TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☐ GAS WELL ☒ OTHER-  
Name of Operator  
Yates Petroleum Corporation  
Address of Operator  
207 South 4th St., Artesia, NM 88210  
Location of Well  
UNIT LETTER K 1980 FEET FROM THE South LINE AND 1980 FEET FROM  
THE West LINE, SECTION 13 TOWNSHIP 17S RANGE 28E NMPM.  
15. Elevation (Show whether DF, RT, GR, etc.)  
3697' GR  
12. County  
Eddy

6. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO:  
PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐ REMEDIAL WORK ☐ ALTERING CASING ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐ COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐  
PULL OR ALTER CASING ☐ OTHER Commence drilling w/rotary tools ☒  
OTHER

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Moved in rotary tools and resumed drilling 17-1/2" hole 1:00 PM 5-26-85. Ran 9 joints 13-3/8" 54.5# J-55 casing set 350'. 1-guide shoe set 350'. Insert float set 311'. Cemented w/350 sx Class "C" + 2% CaCl2. Compressive strength of cement - 1250 psi in 12 hrs. PD 10:30 PM 5-26-85. Bumped plug to 1000 psi, released pressure and float held okay. Cement did not circulate. WOC 6 hrs. Ran 1". Tagged cement 140'. Spotted 50 sacks Class "C" + 4% CaCl2. PD 8:50 AM 5-27-85. WOC 2 hours. Ran 1". Tagged cement 80' (16' fill). Spotted 50 sacks Class "C" + 4% CaCl2. PD 10:55 AM 5-27-85. WOC 2 hours. Ran 1". Tagged cement 70' (10' fill). Spotted 50 sacks Class "C" + 4% CaCl2. PD 12:55 5-27-85. WOC 2 hours. Ran 1". Tagged cement 42'. Spotted 150 sacks Class "C" + 4% CaCl2. PD 3:45 PM 5-27-85. Circulated cement to cellar. WOC. Drilled out 6:15 AM 5-27-85. WOC 19 hrs and 15 mins. Tested casing to 1000 psi for 30 minutes, OK. Reduced hole to 11". Drilled plug and resumed drilling.

8. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED: Francis Goodlett TITLE Production Supervisor DATE 5-30-85

APPROVED BY: Les A. Clements TITLE Supervisor District II DATE JUN 04 1985

CONDITIONS OF APPROVAL, IF ANY: