INSTRUCTIONS

- 4.7

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or despend well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, liens 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico			New Mexico	Northwestern New Mexico			
T. B. T.	Yates	T. T. T. T. T. T. T. T. T. T. T. T. T. T	Canyon 8599 Strawn 9409 Strawn 9978 Atoka 9978 Miss	T. Ojo Alamo T. Kirtland-Fruitland T. Pictured Cliffs T. Cliff House T. Menefee T. Menefee T. Mancos T. Mancos T. Gallup Base Greenhorn T. Dakota T. Dakota T. Todilto T. Todilto T. Entrada T. Wingate T. Chinle T. Permian	T. Penn. "B" T. Penn. "C" T. Penn. "D" T. Penn. "D" T. Leadville T. Leadville T. Leadville T. Leadville T. Leadville T. Madison T. Elbert T. McCracken T. Ignacio Qtzte T. Granite T. T. T. </th		
No.	1, from	4 0 4 6 0 0 4 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 		No. 4, from	to		
No.	2, from			No. 5, from			
No.	3, from		to	No. 6, from	to		

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.									
No. 1,	from								
No. 2	froinfcct.								
No. 3,	from	*************** *********************							
No. 4	from	••••••••••••••••••••••••••••••••••••••							

FORMATION RECORD (Attach additional sheets if necessary)

From	То	Thickness in Feet	Formation	From	То	Thickness in Feet	Formation
0	165	165	Surface	7500	8600	1100	Lime, Shale
165	350	185	Redbeds, Anhy	8600	9100	500	Dolo, Lime
350	2225	1875	Sand, Anhy	9100	9220	120	Dolo, Lime, Shale
2225	2658	433	Anhy, Lime	9220	10110	890	Lime, Shale
2658	3070	412	Dolo	10100	10520	410	Lime, Sand, Shale
3070	3500	430	Dolo, Cht	10520	10760	240	Shale
3500	4160	660	Dolo			· ·	
4160	4446	286	Dolo, Sand				
4446	5180	734	Dolo				
5180	5364	184	Dolo, Sand				
5364	5872	508	Dolo				
5872	6200	328	Dolo, Shale, Anhy				
6200	6970	770	Dolo				· · ·
6970	7210	240	Dolo, Lime				·
7210	7500	290	Lime				
,	1,200				1		
	ļ				Į		l · · · · · · · · · · · · · · · · · · ·