

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐

2. NAME OF OPERATOR

Metex Pipe & Supply

3. ADDRESS OF OPERATOR

P. O. Box 1037 Artesia, N. M. 88210

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 3603' FNL & 2310' FEL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) Plug and abandon

SUBSEQUENT REPORT OF:

SEP 25 1985

5. LEASE

NY-059945

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Sunburst Fed

9. WELL NO.

51

10. FIELD OR WILDCAT NAME

N. SQ. LAKE

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

S-5, T-16S, R-31E

12. COUNTY OR PARISH 13. STATE

Eddy

N. M.

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

4065.2 GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Plugged well in the following manner as per verbal instructions via telephone August 27, 1985, by Bob Pitschke. Work was performed Sept. 21, 1985. BLM was notified via Telephone 2 hours prior to commencing work.

1. Set 15 sack plug, (100 ft plus), Class 'C' cement at 3138. Tagged plug at 3138.
2. Set 200' cement plug at Queen at 2647'
3. Set 100' cement plug at base of salt at 1700'
4. Set 100' cement plug at top of salt at 900'. Tagged plug at 774'.
5. Set 100' cement plug at 311' at surface pipe shoe.
6. Set 50' cement surface plug.
7. Squeezed 5 sx into annulus to assure backside full.

Subsurface Safety Valve: Manu. and Type

Set @

... Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

d/b/a

Metex Pipe & Supply

September 23, 1985

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

Post ID-2
10-3-86
P4A