

Drawer

Artesia, NM 88410

Form 9-331
(May 1983)UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-30067

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Sara Fed.

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat - San Andres

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 10-T16S-R28E

12. COUNTY OR PARISH 13. STATE

Eddy

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ Dry Hole

2. NAME OF OPERATOR

McClellan Oil Corporation

3. ADDRESS OF OPERATOR

P.O. Drawer 730, Roswell, NM 88202

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

1980' FSL & 1980' FEL

RECEIVED BY

DEC 12 1985

O. C. D.
ARTESIA, OFFICE

14. PERMIT NO.

15. ELEVATIONS (Show whether DT, RT, GR, etc.)

3601' G.L.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

Casing & Cement

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)

10/10/85: Moved in Cortez cable tool rig and spudded with 12" bit.

10/16/85: Drilled to 350'. Set 350' of 10-3/4" casing. Cemented with 300 sx
Class C with 2% CaCl₂. Circ.

10/17/85: Drilled out with 10" bit.

10/31/85: Drilled to 732'. Ran 732' of 8-5/8", 20 lb/ft casing. Cemented
with 200 sx Class C with 2% CaCl₂. Circ.

11/06/85: Drilled out with 8" bit.

11/26/85: Drilled to 1845'. Logged with Dresser CNL-Density Log. Shut in.
Prep to abandon.

ACCEPTED FOR RECORD

Hurl
DEC 11 1985

18. I hereby certify that the foregoing is true and correct

SIGNED

V. R. Regis

CARLSBAD, NEW MEXICO

TITLE Operations Manager

DATE 12/6/85

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE