

4/5

Form 9-331
(May 1963)

NM OIL COMS

Drawer DD

UNITED STATES DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

McClellan Oil Corporation

3. ADDRESS OF OPERATOR

P.O. Drawer 730, Roswell, NM 88202

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

1650' FNL & 330' FWL

RECEIVED BY

DEC 23 1985

O. C. D.

ARTESIA, OFFICE

5. LEASE DESIGNATION AND SERIAL NO.

LC-046119-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Renee Fed.

9. WELL NO.

3

10. FIELD AND POOL, OR WILDCAT

High Lonesome Queen

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 20-T16S-R29E

12. COUNTY OR PARISH

Eddy

13. STATE

NM

14. PERMIT NO.

15. ELEVATIONS (Show whether DP, RT, GR, etc.)
3638' G.L.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other) casing & cement

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

12/5/85: Spudded well with 12-1/4" bit. Drilled to 300'.

12/6/85: Ran 7 joints of 8-5/8" 24# casing to 298'. Cemented with Western using 280 sx Class "C" with 2% CaCl₂. Did not circulate cement. Top of cement 30' from surface. Ready mixed with 5 yds. WOC - 18 hours. Nipple up BOP. Test to 1000 psi. Will drill out with 7-7/8" bit.

ACCEPTED FOR RECORD

[Signature]

DEC 19 1985

CARISBAD, NEW MEXICO

18. I hereby certify that the foregoing is true and correct.

SIGNED

[Signature]

TITLE

Production Engineer

DATE

12/17/85

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side