ONITED STATES SUBMIT IN A PLICATE DEPARTMENT OF THE INTERPOR WORKS OF THE LINE OF THE LINE

5. LEASE DEBIGNATION AND BERIAL NO.

Τ,	C-	Λ.	4	6	7	1	9	_	7
ш	ᆫᅳ	U	41	U	ㅗ	_	J	_	t

GEOLOGICAL SURVE¥\$\$\$ 20	LC-046119-A		
SUNDRY NOTICES AND REPORTS ON WELL \$8210 (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)	6. IF INDIAN, ALLOTTEE OR TRIBE NAME		
E. OCL XX WELL DOTHER	7. UNIT AGREEMENT NAME		
McClellan Oil Corporation	Renee Fed.		
P.O. Drawer 730, Roswell, NM 88202	9. WELL NO. 4		
4. LOCKTION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface	10. FIELD AND FOOL, OR WILDCAT High Lonesome _ Duce >- 11. SEC., T., R., M., OR BLK. AND SURVEY OF AREA		

1650' FSL & 330' FWL

Sec. 17-T16S-R29E 14. PERSIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.) 12. COUNTY OR PARISH | 13. STATE 3626' G.L. Eddy 16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INIENTION TO:				SUBSEQUENT REPORT OF:			
	·		r	1			
TAST WATER SHUT-OFF		FULL OR ALTER CASING		WATER SHUT-OFF		REPAIRING WELL	
PHANTERE TREAT		MULTIPLE COMPLETE		PRACTURE TREATMENT		ALTERING CABING	.
SHOWER OR ACIDIZE		ABANDON*		BHOOTING OR ACIDIZING		ABANDONMENT*	
BEPAIR WELL	j	CHANGE PLANS		(Other) Casing	& Cement		
(Other)			<u></u>	(Note: Report feat Completion or Reco	ults of multipompletion Rep	ple completion on Wel	1

SCHIEF PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any next to this work.) (well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and roses pertinent to this work.)

1/3/86: Spud with 12-1/4" bit.

1/4/86: Drilled to 250'. Ran 250' of 8-5/8" 20 lb/ft casing. Cemented with 250 sx Class C with 2% CaCl₂. Did not circulate cement. Ready mixed to surface mixed with 6 yards. WOC - 18 hours. Drilled out with 7-7/8" bit.

1/9/86: Drilled to 1850'. Logged with Dresser CNL-CDL. Ran 1839' of 5-1/2" 14 lb/ft casing. Cemented with 370 sx Class C with 2% CaCl₂. Released rig.

ACCEPTED FOR FECORD

Level JAN 16 1986

CARLSBAD, NEW MEXICO

RECEIVED BY

JAN 17 1986

O. C. D. ARTESIA, OFFICE

hereby certify that the turns the factor and correct		
	Operations Manager	1/10/86 DATE
SPEROVED BY CONSTRUCTIONS OF APPROVAL, IF ANY:	TITLE	DATE