

Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DERIGATION AND SERIAL NO.
NM-41642 ✓
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Exxon Fed.
9. WELL NO.
2 ✓
10. FIELD AND POOL, OR WILDCAT
High Lonesome ✓
11. SEC., T., R., W., OR BLK. AND
SURVEY OR AREA
Sec. 28-T16S-R29E
12. COUNTY OR PARISH 13. STATE
Eddy NM

Form 3-211
(May 1967)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. ☒ OIL WELL ☒ GAS WELL ☐ OTHER

2. NAME OF OPERATOR
McClellan Oil Corporation ✓

3. ADDRESS OF OPERATOR
P.O. Drawer 730, Roswell, NM 88202

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface
990' FNL & 660' FWL

5. PERMIT NO.

6. ELEVATIONS (Show whether DC, RT, OR, etc.)
3635' G.L.

7. RECEIVED BY
FEB 14 1986
O.C.D.
ARTESIA, OFFICE

18. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	☐	WATER SHUT-OFF	☐
FRACTURE TREAT	☐	FRACTURE TREATMENT	☐
SHOOT OR ACIDIZE	☐	SHOOTING OR ACIDIZING	☐
REPAIR WELL	☐	(Other) Casing & Cement	☒
ABANDON	☐	REPAIRING WELL	☐
CHANGE PLANN	☐	ALTERING CASING	☐
		ABANDONMENT	☐

19. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

2/2/86: Drilled to 300' with 12-1/4" bit. Ran 295' of 8-5/8", 20 lb/ft new casing. Cemented with 200 sx Class C with 2% CaCl₂ and 1/4 lb/sx flocele. Circulated cmr. WOC - 18 hours. NU BOP's and test to 1000 psi for 30 minutes. Drill out with 7-7/8" bit.

2/7/86: TD at 2020'. Logged with Dresser CNL-CDL. Ran 2020' of 5-1/2", 14 lb/ft LS casing. Cemented with 380 sx Class C with 2% CaCl₂ and .2% CFR-3. Cement bridged off. Release drilling rig.

ACCEPTED FOR RECORD

SWD
FEB 13 1986

CARLSBAD, NEW MEXICO

20. I hereby certify that the foregoing is true and correct.

SIGNED *Frank R. Rasmussen* TITLE Operations Manager DATE 2/11/86

21. APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: _____

*See Instructions on Reverse Side