

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIP
(Other Instructions
on Reverse Side)

Budget Bureau No. 1004-01.1
Expires August 31, 1985

clsf

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR
McClellan Oil Corporation

3. ADDRESS OF OPERATOR
P.O. Drawer 730, Roswell, NM 88202

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)
At surface
990 FNL & 660 FWL

RECEIVED
MAR 16 '89
O. C. D.
ARTESIA, OFFICE

14. PERMIT NO. _____

15. ELEVATIONS (Show whether DF, RT, GR, etc.)
3635' G.L.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	<input type="checkbox"/>	WATER SHUT-OFF	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	FRACTURE TREATMENT	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	SHOOTING OR ACIDIZING	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	(Other)	<input type="checkbox"/>
(Other)	<input type="checkbox"/>	(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)	<input type="checkbox"/>

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

01/27/89: Rigged up Baber Well Service. Pulled Rods. Set 1st cement plug at 1950' with 25 sx cement. WOC-2 hours, tagged plug at 1837'. Cmt casing at 990 ft and laid casing down. Set 2nd plug at 1040 ft. with 25 sx. Tagged plug at 930 ft. Set 3rd plug at 350' with 25 sx. Tagged plug at 199'. Set 10 sx plug at surface. Installed dry hole marker. Clean location.

Part ID-2
3-24-89
PFA

18. I hereby certify that the foregoing is true and correct

SIGNED Paul Ragdale TITLE Operations Manager DATE February 3, 1989

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE 3-15-89

CONDITIONS OF APPROVAL, IF ANY: _____

*See Instructions on Reverse Side

3D-015-25553

Oxford[®]

ESSENT

MADE IN U.S.A.

NO R753 1/3

6 6 6 6

3-31-86

Acoustic Cement Bond

GR - NDL

950-1774

Comp. Dens. Comp. Neut
GR