orm 9–331			Form approved.
May 1963)	U TED ST DEPARTMENT OF T GEOLOGICAL	HE INTERIOR verse side)	CATE* On re- 5. LEASE DESIGNATION AND SERIAL NO. NM 9987
	DRY NOTICES AND		6. IF INDIAN, ALLOTTEE OR TRIBE NAME
(Do not use this f	orm for proposals to drill or to Use "APPLICATION FOR PER	o deepen or plug back to a university reservoir MIT-" for such proposels);	r.
		AANIS	7. UNIT AGREEMENT NAME
OIL GAS WELL X WELL	OTHER	MAR - 5 1987	8. FARM OR LEASE NAME
	1 Drilling, Inc	9. C h	Max Federal
ADDRESS OF OPERATOR	- · ·	ARTESIA, OFFICE	9. WELL NO.
P.O.BOX LOCATION OF WELL (Re	1393, Roswell, port location clearly and in acc	N.M. 88201 ordance with any State requirements.*	4 10/ FIELD AND FOOL, OR WILDCAT
See also space 17 belov At surface	₩.)		East Red Lake- Q-G
2310 FSL	and 1076' FWL		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
			Sec. 30-T16S-R29E
4. PERMIT NO.		S (Show whether DF, RT, GR, etc.)	12. COUNTY OR PARISH 13. STATE
	3680		Eddy N.M.
3. ·		To Indicate Nature of Notice, Repo	subsequent report of:
-	OTICE OF INTENTION TO:		SUBSEQUENT REPORT OF :
TEST WATER SHUT-OF FRACTURE TREAT	F PULL OR ALTER C MULTIPLE COMPL		
SHOOT OR ACIDIZE	ABANDON*	SHOOTING OR ACIDE	ZING ABANDON MENT*
REPAIR WELL	CHANGE PLANS	(NOTE : Report	rt results of multiple completion on Well
(Other)	(0)	Completion or	r Recompletion Report and Log form.) ent dates, including estimated date of starting any a vastical daths for all markers and some parti-
TD 17 150 s top 8 9 yds	sx Class C, 2% C 30', determined s. ready mix wit	10 3/4" 40.5# casing. aC1. Plug down at 3:0 by wireline. Filled t h 3/8" pea gravel, (a th Bureau of Land Ma	00 p.m. Cemented to surface with as per verbal order
TD 17 150 s top 8 9 yds from	70 ft. Ran 170' sx Class C, 2% C 30', determined s. ready mix wit Mr. Balderez wi	aC1. Plug down at 3:0 by wireline. Filled t	00 p.m. Cemented to surface with as per verbal order
TD 17 150 s top 8 9 yds from	70 ft. Ran 170' sx Class C, 2% C 30', determined s. ready mix wit	aCl. Plug down at 3:0 by wireline. Filled t h 3/8" pea gravel, (a	00 p.m. Cemented to surface with as per verbal order anagement)
TD 17 150 s top 8 9 yds from	70 ft. Ran 170' sx Class C, 2% C 30', determined s. ready mix wit Mr. Balderez wi	aCl. Plug down at 3:0 by wireline. Filled t h 3/8" pea gravel, (a	00 p.m. Cemented to surface with as per verbal order
TD 17 150 s top 8 9 yds from	70 ft. Ran 170' sx Class C, 2% C 30', determined s. ready mix wit Mr. Balderez wi	aCl. Plug down at 3:0 by wireline. Filled t h 3/8" pea gravel, (a	00 p.m. Cemented to surface with as per verbal order anagement)
TD 17 150 s top 8 9 yds from	70 ft. Ran 170' sx Class C, 2% C 30', determined s. ready mix wit Mr. Balderez wi	aCl. Plug down at 3:0 by wireline. Filled t h 3/8" pea gravel, (a	OO p.m. Cemented to surface with as per verbal order anagement) ACCEPTED FOR RECORD
TD 17 150 s top 8 9 yds from	70 ft. Ran 170' sx Class C, 2% C 30', determined s. ready mix wit Mr. Balderez wi	aCl. Plug down at 3:0 by wireline. Filled t h 3/8" pea gravel, (a	00 p.m. Cemented to surface with as per verbal order anagement) ACCEPTED FOR RECORD MAR 0 3 1987
TD 17 150 s top 8 9 yds from W O (70 ft. Ran 170' sx Class C, 2% C 30', determined s. ready mix wit Mr. Balderez wi C 24 hrs.	aCl. Plug down at 3:0 by wireline. Filled t h 3/8" pea gravel, (a th Bureau of Land Ma	DO p.m. Cemented to surface with as per verbal order anagement) ACCEPTED FOR RECORD MAR 031987 JM
TD 17 150 s top 8 9 yds from W O (70 ft. Ran 170' sx Class C, 2% C 30', determined s. ready mix wit Mr. Balderez wi	aCl. Plug down at 3:0 by wireline. Filled t h 3/8" pea gravel, (a th Bureau of Land Ma	00 p.m. Cemented to surface with as per verbal order anagement) ACCEPTED FOR RECORD MAR 0 3 1987 Jm CARLSBAD, NEW MEXICO
TD 17 150 s top & 9 yds from W O (18. I hereby certify that SIGNED	70 ft. Ran 170' sx Class C, 2% C 30', determined s. ready mix wit Mr. Balderez wi C 24 hrs.	aCl. Plug down at 3:0 by wireline. Filled t h 3/8" pea gravel, (a th Bureau of Land Ma	00 p.m. Cemented to surface with as per verbal order anagement) ACCEPTED FOR RECORD MAR 0 3 1987 Jm CARLSBAD, NEW MEXICO
TD 17 150 s top & 9 yds from W O (18. I hereby certify that SIGNED	70 ft. Ran 170' sx Class C, 2% C 30', determined s. ready mix wit Mr. Balderez wi C 24 hrs. the foregoing is true and correct a Job ral or State office use)	aCl. Plug down at 3:0 by wireline. Filled t h 3/8" pea gravel, (a th Bureau of Land Ma	00 p.m. Cemented to surface with as per verbal order anagement) ACCEPTED FOR RECORD MAR 0 3 1987 Jm CARLSBAD, NEW MEXICO

-