

clsf

Form 9-331  
Dec. 1973

RECEIVED  
Drill No. 10  
Artesia, N. 80210

Form Approved.  
Budget Bureau No. 42-R1424

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug a well or to alter a well or to alter a reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well ☐ gas ☒ well ☐ other

2. NAME OF OPERATOR

Pacific Enterprises Oil Company (USA)

3. ADDRESS OF OPERATOR

P.O. Box 3033 Midland, Texas 79702

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE:

AT TOP PROD. INTERVAL: 660' N 1980' W

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF:

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☒

5. LEASE

NM-30067

6. IF INDIAN, ALLOTTEE OR TRIBAL NAME

7. UNIT AGREEMENT DEC 15 1989

8. FARM OR LEASE NAME

Pennzoil 9 Federal

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

Diamond Round

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 9 T16S R28E

12. COUNTY OR PARISH

Eddy

13. STATE

NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3642.7' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

11-28-1989 Set 5150' y 8" casing, 35' cement on top  
11-29-1989 Spot 25' sgs @ 1150' - 1160'  
11-29-1989 Spot 25' sgs @ 1160' - 1170'  
11-30-1989 Spot 35' sgs @ 1170' - 1180' tagged  
11-30-1989 Spot 35' sgs @ 1180' - 1190'  
11-30-1989 Spot 15' sgs @ surface

Pulled 1980' of 5 1/2" casing  
Install dry hole marker  
Hole circulated with 10# mud

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Olanir Bastin TITLE President DATE 12-12-89

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE 12-21-89

CONDITIONS OF APPROVAL, IF ANY:

Approved as to plugging of the well bore.  
Liability under bond is retained until  
surface restoration is completed.

RECEIVED

Post ID-2  
1-12-90  
PFA