

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radioactivity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quadruplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico				Northwestern New Mexico			
		Lower	7021	T. Ojo Alamo		T. Penn. "B"	
T. Anhy		T. Canyon	7284	T. Kirtland-Fruitland		T. Penn. "C"	
T. Salt		T. Strawn	7632	T. Pictured Cliffs		T. Penn. "D"	
U. Salt		T. Atoka	8078	T. Cliff House		T. Leadville	
T. Yates		T. Miss		T. Menefee		T. Madison	
T. 7 Rivers		T. Devonian		T. Point Lookout		T. Elbert	
T. Queen		T. Silurian		T. Mancos		T. McCracken	
T. Grayburg		T. Montoya		T. Gallup		T. Ignacio Qtzite	
T. San Andres		T. Simpson		Base Greenhorn		T. Granite	
T. Glorieta	1898	T. McKee		T. Dakota		T.	
T. Paddeek		T. Ellenburger		T. Morrison		T.	
T. Blinberry	3212	T. Gr. Wash.		T. Todilto		T.	
T. Tubb		T. Granite		T. Entrada		T.	
T. Drinkard		T. Delaware Sand		T. Wingate		T.	
T. Abo	3844	T. Bone Springs		T. Chinle		T.	
T. Wolfcamp	4907	T. Morrow Clastic-7832		T. Permian		T.	
T. Permian U. Canyon-6446		T. Chester	-7949	T. Penn. "A"		T.	
T. Cisco (Bough C)		T.					

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....	No. 4, from.....to.....
No. 2, from.....to.....	No. 5, from.....to.....
No. 3, from.....to.....	No. 6, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....	feet
No. 2, from.....to.....	feet
No. 3, from.....to.....	feet
No. 4, from.....to.....	feet

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	40	40	Surface	6040	6830	790	Lm, Sh
40	80	760	Salt, Anhy, Sd	6830	8300	1470	Lm, Sh, Sd
800	1220	420	Sd, Anhy, Sh				
1220	1460	240	Dolo, Anhy				
1460	1580	120	Dolo, Tr. Cht				
1580	1760	180	Dolo, LS				
1760	2300	540	Dolo, Sd, Anhy				
2300	2530	230	Dolo, Sd, Cht				
2530	2720	190	Dolo				
2720	2860	140	Dolo, Anhy				
2860	3230	370	Dolo, Tr. Cht				
3230	3470	240	Sd, Dolo				
3470	3840	370	Dolo, Tr. Anhy				
3840	4940	1100	Sh, Dolo				
4940	6040	1100	Lm, Sh, Dolo				