Form 9-331 Dec. 1973

> UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

	Form Approved. Budget Bureau No. 42–R1424
	5. LEASE
	NN 2507 6. IF INDIAN, ALLOTTEE OR TRIBE NAME
	7. UNIT AGREEMENT NAME
۱t	8. FARM OR LEASE NAME
	Pegasus Fed.  9. WELL NO.
0	10. FIELD OR WILDCAT NAME AND SURVEY OF AREA
	S-6, T-16S, R-3 IE  12. COUNTY OR PARISH 13. STATE Eddy NM

SUNDRY NOTICES AND REPORTS ON WELLS  (Do not use this form for proposals to drill or to deepRECEIVED k to a different reservoir. Use Form 9-331-C for such proposals.)	7. UNIT AGREEMENT NAME	
reservoir. Use Form 9–331-C for such proposals.)	8. FARM OR LEASE NAME	
1. oil 677 gas (1)	Pegasus Fed.	
well X gas cother APR 19'88	9. WELL NO.	
2. NAME OF OPERATOR		
Metex Pipe & Supply ✓ O. C. D.	10. FIELD OR WILDCAT NAME	
3. ADDRESS OF OPERATOR ARTESIA, OFFICE	N.Squarelake Premier	
2407 Sierra Vista Artesia, N. M. 88210		
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA	
below.) AT SURFACE: 2970' FSL & 635' FWL	S-6, T-16S, R-31E	
AT TOP PROD. INTERVAL:	12. COUNTY OR PARISH 13. STATE	
AT TOTAL DEPTH:	Eddy NM	
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	14. API NO.	
REPORT, OR OTHER DATA	15 SUSTIGNE COLONI DE MODE MADE	
	15. ELEVATIONS (SHOW DF, KDB, AND WD)	
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	3969.3 GL	
TEST WATER SHUT-OFF	(NOTE: Report results of multiple completion or zone change on Form 9–330.)	

200.0

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\* Notified BLM by telephone of intention to spud. Spud well 64:30 PM 4-5-88 with L & M. Drilling Rig II. T.D. 124" surface at 613 ft. Ran 624 ft. 8 5/8, 24#, J-55 casing with shoe at 613 ft. Pumped 400 SX. HALCO Class "C" cement with 4 # flocel and 2% CACL. Plug down at 12:30 PM 4-6-88. Circulated 35 SX. cement to pit. BLM notified & witness was present. Waited 18 hrs. on cement and drilled 2' past shoe and tested BOP to 500 PSI. Pressure held 30 minutes. Drilling 7 7/8 hole 4-7-88.

			RA S	
				73
Subsurface Safety Valve: Manu. and Type		Set @ _	Ft.	CE
18. I hereby certify that the foregoing is t	8	V		
SIGNED THE THE THE	TITLEOperator DATE	4-7-88	4	IVED
	(This space for Federal or State office use)		8	
APPROVED BY CONDITIONS OF APPROVAL, IF ANY:	TITLE DAT	E	· · · · · · · · · · · · · · · · · · ·	
		*** 4.2	1.00	