

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-015-26073
5. Indicate Type of Lease STATE ☒ FEE ☐
6. State Oil & Gas Lease No. LG 3003
7. Lease Name or Unit Agreement Name Richard Knob AEX State
8. Well No. 2
9. Pool name or Wildcat Wildcat Morrow

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT TO DRILL"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL ☐ GAS WELL ☒ OTHER ☐	MAR 30 '89
2. Name of Operator YATES PETROLEUM CORPORATION	
3. Address of Operator 105 South 4th St., Artesia, NM 88210	ARTESIA, OFFICE
4. Well Location Unit Letter K : 1980 Feet From The South Line and 1980 Feet From The West Line Section 34 Township 17S Range 24E NMPM Eddy County	
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3760.2' GR	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK ☐	REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐	ALTERING CASING ☐
PULL OR ALTER CASING ☐	COMMENCE DRILLING OPNS. ☒
OTHER: ☐	PLUG AND ABANDONMENT ☐
	CASING TEST AND CEMENT JOB ☒
	OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 17½" hole 9:15 AM 3-21-89. Ran 6 jts 13-3/8" 54.5# J-55 ST&C csg set 268'. Guide shoe set 268', insert float set 226'. Cemented w/300 sx C1 C+2% CaCl2 (yield 1.32, weight 14.8). PD 9:45 PM 3-21-89. Bumped plug to 1250#, held okay. Circ. 50 sx to surface. WOC 20 hrs, 45 mins. Resumed drilling 12½" hole. Ran 26 jts 8-5/8" 24# J-55 ST&C csg set 1106', guide shoe set 1106' insert float set 1063'. Cemented w/150 sx Pacesetter Lite, 1/2#/sx Celloseal, 10#/sx Gilsonite + 3% CaCl2 (yield 1.84, weight 12.7). Tail in w/150 sx C1 C+2% CaCl (yield 1.32, weight 14.8). PD 2:45 AM 3-24-89. Bumped plug to 1000#, held okay. Cement did not circulate. WOC 6 hrs. Ran Temp. Survey. TOC 640'. Ran 1". Tag cement 630'. Spot 35 sx C1 C+4% CaCl2. PD 1:15 PM 3-24-89. WOC 1½ hrs. Ran 1". Tag cement 583'. Spot 50 sx C1 C+4% CaCl2. PD 2:45 PM 3-24-89. WOC 1½ hrs. Ran 1". Tag cement 356'. Spot 75 sx C1 C+4% CaCl2. PD 4:30 PM 3-24-89. WOC 2 hrs. Ran 1". Tag cement 325'. Spot 50 sx C1 C+4% CaCl2. PD 6:30 PM 3-24-89. WOC 2 hrs. Ran 1". Tag cement 325'. Spot 236 sx C1 C+4% CaCl2. PD 8:30 PM 3-24-89. Circ 10 sx. Drilled out 5:45 AM 3-25-89. WOC 27 hrs. NU and tested to 1000# for 30 mins, OK. Reduced hole to 7-7/8". Drilled plug and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 3-29-89
TYPE OR PRINT NAME Juanita Goodlett TELEPHONE NO. 505/748-1471

(This space for State Use)

Original Signed By
Mike Williams

APR 3 1989

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY: