

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO.  
30-015-26252

5. Indicate Type of Lease  
STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:  
OIL WELL ☐ GAS WELL ☒ OTHER

2. Name of Operator  
Mewbourne Oil Company

3. Address of Operator  
P. O. Box 7698, Tyler, Texas 75711

4. Well Location  
Unit Letter M : 660 Feet From The South Line and 660 Feet From The West Line  
Section 14 Township 17S Range 26E NMPM Eddy County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)  
3319.5' GR

7. Lease Name or Unit Agreement Name  
VOGEL

8. Well No.  
1

9. Pool name or Wildcat  
Und. Kennedy Farms Morrow

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐  
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐  
CASING TEST AND CEMENT JOB ☒  
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. 2/09/90 - TD 8635'. Ran 4-1/2" casing as follows:

Float Shoe	1.00'
1 - Jt. 4-1/2" 11.6# M-75 LT&C	42.00'
Float Collar	2.00'
202 - Jts. 4-1/2" 11.6# M-75 LT&C	8601.00'
Total	8646.00'
KB Correction	11.00'
Set At	8635.00'

Ran 15 centralizers every second joint from bottom. Western cemented with 500 sxs PSL "H" with 5#/sx. Gilsonite, 1/2#/sx. celloseal, 1000 sxs. PSL "H" with 1#/sx. Hi-Seal, 1/2#/sx. Celloseal, 300 sxs. "H" with .6% CF-14, .4% TF-4, 5#/sx. KCL. Flushed w/100 gals 10% acetic acid and 132 bbls 2% KCL water. PD at 1:20 PM to 8590' KB. Circulate 50 sxs. Jet pits and set slips. Release rig 7:00 PM 2/8/90.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Raymond Thompson TITLE Engr. Oprns. Secretary DATE 2/13/90

TYPE OR PRINT NAME

TELEPHONE NO.

(This space for State Use)

ORIGINAL SIGNED BY  
MIKE WILLIAMS

FEB 28 1990

APPROVED BY SUPERVISOR, DISTRICT II

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: