Submit 3 Copies to Appropriate District Office

State of New Mexico Minerals and Natural Resources Department Enc

Form C-103
Revised 1-1

Form C-103
Revised 1-1-89

DISTRICT			
DO Dog 1000	Uabba	N/L/	22711

		MACEMENTON	WELL API NO.
חוכדשוריד וו	P.O. Box 208 Santa Fe, New Mexico		30-015-26452
DISTRICT II P.O. Drawer DD, Artesia, NM 88210	Santa Fe, New Mexico	OCT 2'90	S. Indicate Type of Lease STATE X FEE
DISTRICT III 000 Rio Brazos Rd., Aziec, NM 87410		266	6. State Oil & Gas Lease No.
SUNDRY NOTICES A DO NOT USE THIS FORM FOR PROPOSAL DIFFERENT RESERVOIR. (FORM C-101) FO	7. Lease Name or Unit Agreement Name		
Type of Well:	511 000111 1101 001 20.7		
MET OT MET X	OTHER		PEOC 34 State Comm
Name of Operator			8. Well No.
Pacific Enterprises Oil Co.	(USA)		. 1
Address of Operator P. O. Box 3083, Midland, Te	exas 79702		9. Pool name or Wildcat Empire South (Morrow)
Well Location 2220 Unit Letter J : 2195 Fo			0 Feet From The east Line
Section 34 To	waship 17S Rz	28E	NMPM Eddy County
Section 34 To	10. Elevation (Show whether 3660.3' GR	uge	
. Check Appro	priate Box to Indicate I	Nature of Notice, R	eport, or Other Data
NOTICE OF INTENT	-		SEQUENT REPORT OF:
REORM REMEDIAL WORK L. P	LUG AND ABANDON LI	REMEDIAL WORK	ALTERING CASING
MPORARILY ABANDON C	HANGE PLANS	COMMENCE DRILLING	G OPNS. X PLUG AND ABANDONMENT
ILL OR ALTER CASING		CASING TEST AND C	EMENT JOB
THER:		OTHER:	
 Describe Proposed or Completed Operations (Cl work) SEE RULE 1103. 	early state all pertinent details, ar	d give pertinent dates, incli	iding estimated date of starting any proposed
Spud well at 6:00 AM 9-12-9	90		
Ran and cemented 16 jts. 13 Cemented 13-3/8" with 525	3-3/8", 54.5#, 8rd	, J-55, ST&C ca	asing on 9-12-90 at 513'.
Circulated 140 sx cement to	o surface. WOC 13	-3/4 hrs. Test	ted casing and hydril to
Circulated 140 sx cement to 1000 psig. Ran and cemented 61 jts. 'Cemented 9-5/8" with 1200 if ollowed by 160 sx Premium	o surface. WOC 13 9-5/8", 36#, 8rd, sx Premium Plus HL Plus cement. Cir	-3/4 hrs. Test J-55, ST&C cas: C cement with 6 culated 165 sx	ing on 9-18-90 at 2625. % gel and 10#/sx salt, to surface. WOC 18-1/2
Circulated 140 sx cement to 1000 psig. Ran and cemented 61 jts. Cemented 9-5/8" with 1200 followed by 160 sx Premium hrs. Tested BOP to 2500 p	9-5/8", 36#, 8rd, sx Premium Plus HL Plus cement. Cir sig, rams to 2500	-3/4 hrs. Test J-55, ST&C cas: C cement with 6 culated 165 sx psig and annula	ing on 9-18-90 at 2625. % gel and 10#/sx salt, to surface. WOC 18-1/2
Circulated 140 sx cement to 1000 psig. Ran and cemented 61 jts. Cemented 9-5/8" with 1200 followed by 160 sx Premium hrs. Tested BOP to 2500 ps	9-5/8", 36#, 8rd, sx Premium Plus HL Plus cement. Cirsig, rams to 2500	-3/4 hrs. Test J-55, ST&C cas: C cement with 6 culated 165 sx psig and annula	ing on 9-18-90 at 2625'. % gel and 10#/sx salt, to surface. WOC 18-1/2 ar to 2000 psig.

MIKE WILLIAMS

SUPERVISOR DISTRICT IS THE

APPROVED BY -