

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

MAR 5 1991

O. C. D.
ARTESIA, OFFICE

WELL API NO.

30-015-26452

5. Indicate Type of Lease

STATE ☒

FEE ☐

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

PROC. "34" State Comm

8. Well No.

1

9. Pool name or Wildcat

Empire South Morrow

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☐

GAS
WELL ☒

OTHER

2. Name of Operator

Bettis, Boyle & Stovall

3. Address of Operator

P.O. Box 1240, Graham, Texas 76046

4. Well Location

Unit Letter J : 2220 Feet From The south

Line and 1765

Feet From The east

Line

Section 34

Township 175

Range 28E

NMPM Eddy

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3660.3' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: Plug Back & Complete ☒

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. Move-in and rig up completion equipment.
2. Run and set a CIBP at 10,235' KB, dump 35 feet of cement on plug;
3. run and set a CIBP at 9816' KB, dump 35 feet of cement on plug.
4. Spot 250 gallons of 10% acetic acid at 8980' KB.
5. Perforate 8868', 8883', 8924', 8968' 8980' KB (5 shots).
6. Displace acid; swab and/flow to clean-up and test.
7. Acidize with 2500 gallons of 20% NeFe acid, swab/flow to clean-up and test.
8. Install surface production equipment.
9. Run 4 point test.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE

DATE

TYPE OR PRINT NAME

TELEPHONE NO.

(This space for State Use)

ORIGINAL SIGNED BY

MIKE WILLIAMS

APPROVED BY

SUPERVISOR, DISTRICT II

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

MAR 28 1991