

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

RECEIVED

APR 15 1991

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88207

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088

San Jose, New Mexico 87504-2088

WELL/API NO.

ARTEZIA, 304015-26628

5. Indicate Type of Lease

STATE ☐

FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☐

GAS
WELL ☒

OTHER

2. Name of Operator

Mewbourne Oil Company

3. Address of Operator

P. O. Box 7698, Tyler, Texas 75711

4. Well Location

Unit Letter E : 1980 Feet From The North Line and 660 Feet From The West Line

Section 14 Township 17S Range 26E NMPM Eddy County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3323.5' GR

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☒

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☒

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

3/12/91 - Spud at 2:00 PM 3/12/91.

3/16/91 - Ran 11 jts 13-3/8" 48# ST&C new casing set at 467' cemented w/100 sxs Thixset + 5# Gilsonite + 1/2# Flocele + 2% CaCl and 400 sxs Halco with 5# Gilsonite + 1/2# Flocele + 2% CaCl and 300 sxs Class "C" w/2% CaCl. Plug down at 4:30 PM. Cement did not circulate. WOC 18-3/4 hrs.

3/17/91 - Cemented thru 1" in six stages, 48 yards pea gravel + 35 yards redi-mix down back-side of 13-3/8" casing. Used 210 sacks Class "C" cement.

3/18/91 - Ran 40 jts 8-5/8" 24# J-55 ST&C new casing set at 1390' cemented with 100 sxs Prem Class "C" thixset w/1/2# Flocele + 5# Gilsonite + 2% CaCl and 400 sxs lite, 5# Gilsonite + 2% CaCl + 1/4# Flocele and 250 sxs Class "C" w/2% CaCl. Plug down at 7:00. Cement did not circulate.

3/19/91 - TTH w/1". Tagged cmt @ 542'. Cmt @ 530' w/50 sxs Class "C" 2/3% CaCl. 2nd stage w/200 sxs Class "C" w/4% CaCl. Hole circ. WOC 2 hrs. WTH & tagged up at 520'. Cmt @ 471' w/250 sxs Class "C" w/3% CaCl. Circ 8 bbls to pit. WOC 24 hrs. Press test 1000#-30 mins.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Held okay.

SIGNATURE

TITLE

Engr. Opns. Secretary

DATE 3/21/91

TYPE OR PRINT NAME

TELEPHONE NO.

(This space for State Use)

ORIGINAL SIGNED BY
MIKE WILLIAMS

APPROVED BY

SUPERVISOR, DISTRICT II

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

MAY 10 1991