

prevent erosion, maintain good drainage, and to be consistent with local drainage patterns. BLM may specify any additions or changes during the onsite inspection.

- B. The average grade will be less than 3%.
- C. No turnouts are planned.
- D. No culverts, cattleguards, gates, low-water crossings, or fence cuts are necessary.
- E. Surfacing material will consist of native caliche. Caliche for surfacing material should come from the location itself. In the event surfacing material is not available from the location, caliche will be obtained from the nearest pit available whether that pit is on private, state, or a BLM approved pit.
- F. The proposed access road as shown in Exhibit #3 has been centerline flagged by the surveyors.

3. Location of Existing Wells:

Exhibit #4 with attachment shows wells within a one-half mile radius of the proposed well and lists them.

4. Location of Existing and/or Proposed Facilities:

- A. No existing facilities are where the proposed well is staked. (See Exhibit #5)
- B. If the well is productive, contemplated facilities will be as follows:
  - (1.) Gas Well Completion: Production equipment necessary for a gas well production will consist of a 500MM BTU, 3 phase gas production unit, a 210 bbl. fiberglass water tank, and a 300 bbl. steel production tank.
  - (2.) Any additional caliche required for firewalls or tank pads will either come from the location itself or from other sources cited in item #2, subparagraph "E".
  - (3.) No power will be required if the well is productive of gas. However, if productive of oil, it may be necessary to run an electric power line down existing road R-O-W.