

RECEIVED

M. GLE COFF. CORPORATION  
Drawer 10Form 3160-5  
(June 1990)UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

AUG 9 11 12 AM '93

CARD

## SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposalsFORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

5. Lease Designation and Serial No.

LC-057798

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Chalk Bluff "35" Fed. #1

9. API Well No.

30-015-27224

10. Field and Pool, or Exploratory Area

Illinois Camp Morrow North

11. County or Parish, State

Eddy Co. N.M.

SUBMIT IN TRIPLICATE

RECEIVED

SEP - 8 1993

O.C.D.

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Mewbourne Oil Company

3. Address and Telephone No.

P.O. Box 5270 Hobbs, New Mexico (505) 393-5905

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FSL & 1980' FEL  
Sec. 35-T17S-R27E

## 12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

## TYPE OF SUBMISSION

- ☐
- Notice of Intent
- 
- ☒
- Subsequent Report
- 
- ☐
- Final Abandonment Notice

## TYPE OF ACTION

- ☐
- Abandonment
- 
- ☐
- Recompletion
- 
- ☐
- Plugging Back
- 
- ☐
- Casing Repair
- 
- ☐
- Altering Casing
- 
- ☒
- Other Cement 5-1/2" Prod.
- 
- Csg.
- 
- ☐
- Change of Plans
- 
- ☐
- New Construction
- 
- ☐
- Non-Routine Fracturing
- 
- ☐
- Water Shut-Off
- 
- ☐
- Conversion to Injection
- 
- ☐
- Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

08/02/93 T.D. 8-3/4" hole @ 9963'. Ran 232 Jts. of new and used 17#, API, 8rd, LT&C, S-95 & K-55, 5-1/2" casing. Western cemented first stage w/575 sks. of Pacesetter Lite "C" containing 6% gel + 1/2#/sk. celloseal + 2#/sk Gilsonite followed by 250 sks. of Class "H" containing 5#/sk. CSE + 3#/sk. salt + .7% CF-14. Opened D.V. tool @ 6656' and cmtd. second stage w/1,020 sks of Pacesetter Lite "C" containing 6% gel + 1/2#/sk. celloseal + 2#/sk. CSE + 5#/sk. salt followed by 500 sks. of Class "C" containing 5#/sk. CSE + 3#/sk. salt + .4% CF-14. Plug down to 6656' @ 7:30 p.m. 08/02/93. Set slips and released rig @ 4:00 a.m. 08/03/93.

14. I hereby certify that the foregoing is true and correct

Signed

*Bill Pierce*

Title

Drlg. Supt.

Date

08/06/93

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\*See Instruction on Reverse Side

C15F