

ATTACHMENT VI-3

TOP OF CEMENT IN INJECTION ZONE WELLS IN THE AREA OF REVIEW

Map ID No.	Casing Diameter (inches)	Setting Depth (feet)	Cement Volume (sacks)	Hole Diameter (inches)	Cement Factor (cu ft/sacks)	Hole Rugosity	Cement Height (feet)	Top of Cement (feet below ground)
81	13.375	663	650	17.5	1.1	0.8	823	Surface
	8.625	4000	1400	11	1.1	0.8	4846	Surface
	5.5	10450	2007	7.875	1.1	0.8	10194	256
83*	13.375	354	350	17.5	1.1	0.8	443	Surface
	8.625	1745	650	.11	1.1	0.8	2250	Surface
	5.5	8466	520	7.875				6250 ¹
124**	13.375	400	500	17.5	1.1	0.8	633	Surface
	9.625	2600	1100	12.25	1.1	0.8	3091	Surface
	7	9445	1895	7.875	1.1	0.8	23491	Surface
	4.5	10198	175	6.125	1.1	0.8	1635	Top of Liner
134	13.375	416	450	17.5	1.1	0.8	570	Surface
	9.625	2610	1025	12.25	1.1	0.8	2880	Surface
	5.5	10148	1020	8.75	1.1	0.8	3554	6594
144	13.375	400	100	17.5	1.1	0.8	127	273
	9.625	2600	250	12.25	1.1	0.8	702	1898
	7	8968	1200	8.75	1.1	0.8	7025	1943
	4.5	10150	200	6.125	1.1	0.8	1869	Top of Liner
157	13.375	400	425	17.5	1.1	0.8	538	Surface
	9.625	2604	1025	12.25	1.1	0.8	2880	Surface
	7	9450	1350	8.75	1.1	0.8	7903	1547
	4.5	10119	175	6.125	1.1	0.8	1635	Top of Liner