

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

OCT - 4 1993

WELL API NO. 30-015-27619
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State, Oil & Gas Lease No. 647
7. Lease Name or Unit Agreement Name Arco State 26
8. Well No. 1
9. Pool name or Wildcat Artesia-Q-G-SA

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	
2. Name of Operator SDX RESOURCES, INC.	
3. Address of Operator P. O. BOX 5061, MIDLAND, TX 79704	
4. Well Location Unit Letter K : 1650 Feet From The South Line and 1650 Feet From The West Line Section 26 Township 17-S Range 28-E NMPM EDDY County	
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3655 GR	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data			
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:		
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>		CASING TEST AND CEMENT JOB <input type="checkbox"/>	
OTHER: <input type="checkbox"/>		OTHER: <input type="checkbox"/>	

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

09-19-93 Spudded and drilled 532' of 12 1/4" hole. Ran 13 jts of 8 5/8", 24#, J-55 csg set at 530'. Cemented with 200 sx Lite with 1/4#/sx Floccel and 175 sx Class "C" with 2% CACL, Tag cement with wireline at 67' and ready mix with 3 1/2 yds to surface. Pressure tested casing at 1000 PSI for 30 min. Held okay. WOC for 18 hours.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Barbara E. Wickham TITLE Prod. Analyst DATE 09-29-93
TYPE OR PRINT NAME Barbara E. Wickham TELEPHONE NO. 685-1761

(This space for State Use)

ORIGINAL SIGNED BY
MIKE WILLIAMS
SUPERVISOR, DISTRICT I

APPROVED BY _____ TITLE _____ DATE OCT 19 1993

CONDITIONS OF APPROVAL, IF ANY: