

Form 3160-5  
(June 1990)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

RECEIVED

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Mewbourne Oil Company

3. Address and Telephone No.

P.O. Box 5270 Hobbs, New Mexico 88241 (505) 393-5905

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

2140' FWL & 1667' FNL Unit "F"  
Sec. 26-T16S-R28E

FORM APPROVED

Budget Bureau No. 1004-0135  
Expires: March 31, 1993

5. Lease Designation and Serial No.

NM-83066

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Vandagriff "26" Fed. #1

9. API Well No.

30-015-27883

10. Field and Pool, or Exploratory Area

Vandagriff Keyes Queen

11. County or Parish, State

Eddy Co. N.M.

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☒ Other Spud & Cmt. 8-5/8"  
Surface Casing

- ☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

07/08/94 MIRU CapStar Drilling Company, Rig #2. Spudded 12-1/4" surface hole @ 10:00 P.M. 07/08/94

07/09/94 Drilled 12-1/4" surface hole to 305' KB. Ran 7 jts. of new 8-5/8", 24#, J-55, 8rd, ST&C casing and set @ 305' KB. Halliburton cemented w/200 sacks of Class "C" Neet containing 2% CaCl<sub>2</sub>. Plug down to 262' @ 4:30 A.M. 07/09/94. Circulated 65 sacks of cement to the pit. WOC 16 1/2 hours. NU BOP and tested to 500# for 30 minutes. Held ok.

14. I hereby certify that the foregoing is true and correct

Signed

*Bill Prince*

Title Drilling Superintendent

Date 07/11/94

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

Date