

Form 3160-1
(June 1990)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

NM OIL CONS COMMISSION

Drawer DD

Artesia, NM 88310

FORM APPROVED

Budget Bureau No 1004-0135

Expires March 31, 1993

5. Lease Designation and Serial No

NM-83066

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Vandagriff "26" Fed. #1

9. API Well No.

10. Field and Pool, or Exploratory Area

Vandagriff Keyes Queen

11. County or Parish, State

Eddy County, N.M.

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Mewbourne Oil Company

3. Address and Telephone No.

P.O. Box 5270 Hobbs, New Mexico 88241 (505) 393-5905

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

2140' FWL & 1667' FNL
Sec. 26-T16S-R28E

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☒ Other Initial Completion

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Date

7-19-94

Operation

MIRU workover rig. Displaced hole. Ran casing bond log. Perforated Premier Sand from 2,035'-2,053', 2SPF. RIH with PKR and set at 1,940'. Swabbed well with no recovery.

7-20-94

Acidized Premier Sand with 2,000 gals 10% acetic acid. Swabbed well with no recovery.

7-21-94

Set CIBP at 1,975'. Dumped 35' of cement on top of plug with bailer. Perforated Lower Penrose Sand from 1,527'-1,537', 2 SPF. RIH with PKR and set at 1,440'.

7-22-94

Acidized Lower Penrose perfs with 1,500 gals 7 1/2% HCl acid. Swabbed.

7-28-94

Fracced Lower Penrose Sand with 18,500 gals linear gel with 33,500# prop. Swabbed well.

7-30-94

Tripped tbg and put well on pump. Btm of tbg at 1,571'. Started pumping well to pit.

14. I hereby certify that the foregoing is true and correct

Signed

Title Engineer

Date August 10, 1994

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

SJS

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side