

FIELD REPORT FOR CEMENTING OF WELLS

OIL CONSERVATION DIVISION

30-015-28607

Operator <u>Medallion Prod Co</u>		Lease <u>Lewis 19</u>		Well # <u>1</u>	
Location of Well	Unit <u>K</u>	Section <u>19</u>	Township <u>17</u>	Range <u>26</u>	County <u>Elly</u>
Drilling Contractor	<u>NA</u>		Type of Equipment <u>R</u>		

APPROVED CASING PROGRAM

* Witness

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>17 1/2</u>	<u>13 3/8</u>	<u>48 #</u>		<u>500</u>	<u>425 Circ</u>
<u>13 1/4</u>	* <u>8 5/8</u>	<u>24 #</u>		<u>1560</u>	<u>850 Circ</u>
<u>7 7/8</u>	<u>4 1/2</u>	<u>11.6 #</u>		<u>8300</u>	<u>360</u>

Casing Data:

Surface 30 joints of 8 5/8 inch 24 # Grade J-55

(Approved) (Rejected)

Inspected by Ken Livingston date 9-8-95

Cementing Program

Size of hole 12 1/4 Size of Casing 8 5/8 Sacks cement required 850 circType of Shoe used Guid Float collar used insert Btm 3 jts welded yesTD of hole 1345 Set 1345 Feet of 8 5/8 Inch 24 # Grade J-55New-used csg. @ 1345 with 200 / 100 sacks neat cement around shoe+ 525 sax 35/65 P02 additives 6% Gel 2% CaCl2 1/4 / 5 x celloflakePlug down @ 11:45 (AM) (PM) Date 9-8-95Cement circulated yes No. of Sacks 79Cemented by Dowell Witnessed by Ken Livingston

Temp. Survey ran @ (AM) (PM) Date top cement @

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks:

L. C 1086 DB 1140 to 1066 RT