

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

0158  
Form C-103  
Revised 1-1-89

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

OIL CONSERVATION DIVISION

2040 Pacheco St.  
Santa Fe, NM 87505

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

WELL API NO. 30-015-28946
Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
State Oil & Gas Lease No.
Lease Name or Unit Agreement Name Dinah 23 Federal Com
Well No. 1
Pool name or Wildcat South Empire-Morrow Gas Pool

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER	
Name of Operator Ricks Exploration, Inc.	
Address of Operator 210 Park Ave., Suite 3000, Oklahoma City, OK 73102	
Well Location Unit Letter M : 1077' Feet From The South Line and 660' Feet From The West Line Section 23 Township 17S Range 28E NMPM Eddy County	
Elevation (Show whether DF, RKB, RT, GR, etc.) GL: 3590'	

11

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:


PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐  
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ PLUG AND ANBANDONMENT ☐  
CASING TEST AND CEMENT JOB ☐  
OTHER: Adding perf's, diff resvr ☒

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

ND wellhead & install double BOP w/tbg & blind rams.  
TIH w/Packer and squeeze Wolfcamp perfs 7862-72', drill out cmt & test, drill out CIBP @9806'. Fish TCP guns, TIH w/Packer & squeeze Atoka perfs 9810-9817', drill out cmt, & test to 1000 psi. Add Morrow perfs 10163-69', 10322-26', 10332-38' to existing perfs 10224-10252'. Set Halliburton 5-1/2" WPL Retrievable Packer w/rupture disk @10083' Perform BHP test, & state test.



I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Lynne Suchy TITLE Drilling Asstnt DATE 8/2/01  
TYPE OR PRINT NAME Lynne Suchy TELEPHONE NO. 405/5161100

(This space for State Use)

APPROVED BY BA ORIGINAL SIGNED BY TIM W. GUN DISTRICT II SUPERVISOR TITLE DATE SEP 4 2001

CONDITIONS OF APPROVAL, IF ANY: