Form 3160-5 (June 1990)

UN 'D STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED

Da mak was this forms for many scale to shall .	S AND REPORTS ON WELLS	5. Lease Designation and Serial No.
Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.		LC-064050-A
Use "APPLICATION Fo	OR PERMIT—" for such proposals	6. If Indian, Allottee or Tribe Name
SUBMIT IN TRIPLICATE		NA
1. Type of Well		7. If Unit or CA, Agreement Designation
Oil Gas Gas Well ☐ Other	DEC 09 '96	N/A
2. Name of Operator	DLC 0 7 30	8. Well Name and No.
DEVON ENERGY CORPORATION (NEV	(ADA) O. C. D.	Eagle "34I" Federal #17
3. Address and Telephone No.	ARTESIA, OFFICE	9. API Well No.
20 NORTH BROADWAY, SUITE 1500, O	OKLAHOMA CITY, OKLAHOMA 73102 (405) 235-3611	30-015-29091
4. Location of Well (Footage, Sec., T., R., M., or Survey	y Description)	10. Field and Pool, or Exploratory Area
2310' FSL & 990' FEL (I) of Section 34-T17S-R27E		Red Lake (Q-GB-SA)
		11. County or Parish, State
		Eddy County, NM
CHECK APPROPRIATE BOX(s	s) TO INDICATE NATURE OF NOTICE, REF	PORT, OR OTHER DATA
TYPE OF SUBMISSION	TYPE OF ACTION	
Notice of Intent	Abandonment	Change of Plans
	Recompletion	New Construction
Subsequent Report	☐ Plugging Back ☐ Casing Repair	☐ Non-Routine Fracturing ☐ Water Shut-Off
Final Abandonment Notice	Altering Casing	Conversion to Injection
	Other <u>Completion</u>	Dispose Water
		(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)
Describe Proposed or Completed Operations (Clearly state all subsurface locations and measured and true vertical depths	pertinent details, and give pertinent dates, including estimated date of starting for all markers and zones pertinent to this work.)*	Completion or Recompletion Report and Log form.)
Describe Proposed or Completed Operations (Clearly state all subsurface locations and measured and true vertical depths	bertinent details, and give pertinent dates, including estimated date of startin s for all markers and zones pertinent to this work.)*	Completion or Recompletion Report and Log form.)
subsurface locations and measured and true vertical depths	s for all markers and zones pertinent to this work.)*	Completion or Recompletion Report and Log form.) g any proposed work. If well is directionally drilled, give
subsurface locations and measured and true vertical depths 11/5/96 RU Wedge WL. Ran Bond Ic	og from 2550' to surf. Perf'd w/1 SPF as foll	Completion or Recompletion Report and Log form.) g any proposed work. If well is directionally drilled, give lows: 1938', 56', 64', 82', 96', 98',
subsurface locations and measured and true vertical depths 11/5/96 RU Wedge WL. Ran Bond lo 2022', 73', 2108', 20', 42', 64', 88', 90	og from 2550' to surf. Perf'd w/1 SPF as foll ', 2200', 12', 22', 34', 44', 78', 85', 2300', 02	Completion or Recompletion Report and Log form.) g any proposed work. If well is directionally drilled, give lows: 1938', 56', 64', 82', 96', 98',
subsurface locations and measured and true vertical depths 11/5/96 RU Wedge WL. Ran Bond lo 2022', 73', 2108', 20', 42', 64', 88', 90	og from 2550' to surf. Perf'd w/1 SPF as foll ', 2200', 12', 22', 34', 44', 78', 85', 2300', 02	Completion or Recompletion Report and Log form.) g any proposed work. If well is directionally drilled, give lows: 1938', 56', 64', 82', 96', 98',
11/5/96 RU Wedge WL. Ran Bond lo 2022', 73', 2108', 20', 42', 64', 88', 90 2385', for a total of 30 holes (.40" EH	og from 2550' to surf. Perf'd w/1 SPF as foll', 2200', 12', 22', 34', 44', 78', 85', 2300', 02 HD Holes).	Completion or Recompletion Report and Log form.) g any proposed work. If well is directionally drilled, give lows: 1938', 56', 64', 82', 96', 98',
11/5/96 RU Wedge WL. Ran Bond lo 2022', 73', 2108', 20', 42', 64', 88', 90 2385', for a total of 30 holes (.40" EH	og from 2550' to surf. Perf'd w/1 SPF as foll ', 2200', 12', 22', 34', 44', 78', 85', 2300', 02	Completion or Recompletion Report and Log form.) g any proposed work. If well is directionally drilled, give lows: 1938', 56', 64', 82', 96', 98',
11/5/96 RU Wedge WL. Ran Bond lo 2022', 73', 2108', 20', 42', 64', 88', 90 2385', for a total of 30 holes (.40" EF Acidize San Andres perfs 1938-2385'	og from 2550' to surf. Perf'd w/1 SPF as follow; 2200', 12', 22', 34', 44', 78', 85', 2300', 02 HD Holes). w/2500 gals of 15% NeFe acid, ISIP 660#.	Completion or Recompletion Report and Log form.) g any proposed work. If well is directionally drilled, give lows: 1938', 56', 64', 82', 96', 98', i', 06', 12', 40', 42', 47', 50', &
subsurface locations and measured and true vertical depths 11/5/96 RU Wedge WL. Ran Bond location 2022', 73', 2108', 20', 42', 64', 88', 90 2385', for a total of 30 holes (.40" EF Acidize San Andres perfs 1938-2385' Frac'd perfs 1938-2385' w/1,000 gals	og from 2550' to surf. Perf'd w/1 SPF as foll ', 2200', 12', 22', 34', 44', 78', 85', 2300', 02 HD Holes). w/2500 gals of 15% NeFe acid, ISIP 660#. PrePad + 2 drum Pro-Kem scale inhibitor + 1	Completion or Recompletion Report and Log form.) g any proposed work. If well is directionally drilled, give lows: 1938', 56', 64', 82', 96', 98', i', 06', 12', 40', 42', 47', 50', &
subsurface locations and measured and true vertical depths 11/5/96 RU Wedge WL. Ran Bond location 2022', 73', 2108', 20', 42', 64', 88', 90 2385', for a total of 30 holes (.40" EF Acidize San Andres perfs 1938-2385' Frac'd perfs 1938-2385' w/1,000 gals	og from 2550' to surf. Perf'd w/1 SPF as foll ', 2200', 12', 22', 34', 44', 78', 85', 2300', 02 HD Holes). w/2500 gals of 15% NeFe acid, ISIP 660#. PrePad + 2 drum Pro-Kem scale inhibitor + 1	Completion or Recompletion Report and Log form.) g any proposed work. If well is directionally drilled, give lows: 1938', 56', 64', 82', 96', 98', i', 06', 12', 40', 42', 47', 50', &
11/5/96 RU Wedge WL. Ran Bond log 2022', 73', 2108', 20', 42', 64', 88', 90 2385', for a total of 30 holes (.40" EF Acidize San Andres perfs 1938-2385' Frac'd perfs 1938-2385' w/1,000 gals mesh sand + 240,000# 20/40 Brady san	og from 2550' to surf. Perf'd w/1 SPF as follow; 2200', 12', 22', 34', 44', 78', 85', 2300', 02 HD Holes). w/2500 gals of 15% NeFe acid, ISIP 660#. PrePad + 2 drum Pro-Kem scale inhibitor + 1 and ISIP 980#, closed at 770#.	Completion or Recompletion Report and Log form.) g any proposed work. If well is directionally drilled, give lows: 1938', 56', 64', 82', 96', 98', 1', 06', 12', 40', 42', 47', 50', & 180,000 gals gel water + 6000# 100
11/5/96 RU Wedge WL. Ran Bond log 2022', 73', 2108', 20', 42', 64', 88', 90 2385', for a total of 30 holes (.40" EF Acidize San Andres perfs 1938-2385' Frac'd perfs 1938-2385' w/1,000 gals mesh sand + 240,000# 20/40 Brady san	og from 2550' to surf. Perf'd w/1 SPF as foll ', 2200', 12', 22', 34', 44', 78', 85', 2300', 02 HD Holes). w/2500 gals of 15% NeFe acid, ISIP 660#. PrePad + 2 drum Pro-Kem scale inhibitor + 1	Completion or Recompletion Report and Log form.) g any proposed work. If well is directionally drilled, give lows: 1938', 56', 64', 82', 96', 98', 1', 06', 12', 40', 42', 47', 50', & 180,000 gals gel water + 6000# 100
11/5/96 RU Wedge WL. Ran Bond log 2022', 73', 2108', 20', 42', 64', 88', 90 2385', for a total of 30 holes (.40" EH Acidize San Andres perfs 1938-2385' Frac'd perfs 1938-2385' w/1,000 gals mesh sand + 240,000# 20/40 Brady san Ran 2 7/8" production tbg, SN set at 24	og from 2550' to surf. Perf'd w/1 SPF as follow; 2200', 12', 22', 34', 44', 78', 85', 2300', 02 HD Holes). w/2500 gals of 15% NeFe acid, ISIP 660#. PrePad + 2 drum Pro-Kem scale inhibitor + 1 and. ISIP 980#, closed at 770#. 403'. Ran pump and rods. Began pump testing.	Completion or Recompletion Report and Log form.) g any proposed work. If well is directionally drilled, give lows: 1938', 56', 64', 82', 96', 98', 1', 06', 12', 40', 42', 47', 50', & 180,000 gals gel water + 6000# 100
11/5/96 RU Wedge WL. Ran Bond log 2022', 73', 2108', 20', 42', 64', 88', 90 2385', for a total of 30 holes (.40" EF Acidize San Andres perfs 1938-2385' Frac'd perfs 1938-2385' w/1,000 gals mesh sand + 240,000# 20/40 Brady san	og from 2550' to surf. Perf'd w/1 SPF as follow, 2200', 12', 22', 34', 44', 78', 85', 2300', 02 HD Holes). w/2500 gals of 15% NeFe acid, ISIP 660#. PrePad + 2 drum Pro-Kem scale inhibitor + 10 ind. ISIP 980#, closed at 770#. 403'. Ran pump and rods. Began pump testing.	Completion or Recompletion Report and Log form.) g any proposed work. If well is directionally drilled, give lows: 1938', 56', 64', 82', 96', 98', 1', 06', 12', 40', 42', 47', 50', & 180,000 gals gel water + 6000# 100
11/5/96 RU Wedge WL. Ran Bond log 2022', 73', 2108', 20', 42', 64', 88', 90 2385', for a total of 30 holes (.40" EH Acidize San Andres perfs 1938-2385' Frac'd perfs 1938-2385' w/1,000 gals mesh sand + 240,000# 20/40 Brady san Ran 2 7/8" production tbg, SN set at 24	og from 2550' to surf. Perf'd w/1 SPF as follow; 2200', 12', 22', 34', 44', 78', 85', 2300', 02 HD Holes). w/2500 gals of 15% NeFe acid, ISIP 660#. PrePad + 2 drum Pro-Kem scale inhibitor + 1 and. ISIP 980#, closed at 770#. 403'. Ran pump and rods. Began pump testing.	Completion or Recompletion Report and Log form.) g any proposed work. If well is directionally drilled, give lows: 1938', 56', 64', 82', 96', 98', 1', 06', 12', 40', 42', 47', 50', & 180,000 gals gel water + 6000# 100
11/5/96 RU Wedge WL. Ran Bond Ic 2022', 73', 2108', 20', 42', 64', 88', 90 2385', for a total of 30 holes (.40" EF Acidize San Andres perfs 1938-2385' Frac'd perfs 1938-2385' w/1,000 gals mesh sand + 240,000# 20/40 Brady san Ran 2 7/8" production tbg, SN set at 24 14. I hereby certify that the foregoing is true and correct Signed	og from 2550' to surf. Perf'd w/1 SPF as follow, 2200', 12', 22', 34', 44', 78', 85', 2300', 02 HD Holes). w/2500 gals of 15% NeFe acid, ISIP 660#. PrePad + 2 drum Pro-Kem scale inhibitor + 10 ind. ISIP 980#, closed at 770#. 403'. Ran pump and rods. Began pump testing.	Completion or Recompletion Report and Log form.) g any proposed work. If well is directionally drilled, give lows: 1938', 56', 64', 82', 96', 98', 1', 06', 12', 40', 42', 47', 50', & 180,000 gals gel water + 6000# 100
11/5/96 RU Wedge WL. Ran Bond log 2022', 73', 2108', 20', 42', 64', 88', 90 2385', for a total of 30 holes (.40" EH Acidize San Andres perfs 1938-2385' Frac'd perfs 1938-2385' w/1,000 gals mesh sand + 240,000# 20/40 Brady san Ran 2 7/8" production tbg, SN set at 24 14. Thereby certify that the foregoing is true and correct	og from 2550' to surf. Perf'd w/1 SPF as follow, 2200', 12', 22', 34', 44', 78', 85', 2300', 02 HD Holes). w/2500 gals of 15% NeFe acid, ISIP 660#. PrePad + 2 drum Pro-Kem scale inhibitor + 1 and. ISIP 980#, closed at 770#. 403'. Ran pump and rods. Began pump testi	Completion or Recompletion Report and Log form.) g any proposed work. If well is directionally drilled, give lows: 1938', 56', 64', 82', 96', 98', 1', 06', 12', 40', 42', 47', 50', & 180,000 gals gel water + 6000# 100 ng.
11/5/96 RU Wedge WL. Ran Bond Ic 2022', 73', 2108', 20', 42', 64', 88', 90 2385', for a total of 30 holes (.40" EF Acidize San Andres perfs 1938-2385' Frac'd perfs 1938-2385' w/1,000 gals mesh sand + 240,000# 20/40 Brady san Ran 2 7/8" production tbg, SN set at 24 14. I hereby certify that the foregoing is true and correct Signed	og from 2550' to surf. Perf'd w/1 SPF as follow, 2200', 12', 22', 34', 44', 78', 85', 2300', 02 HD Holes). w/2500 gals of 15% NeFe acid, ISIP 660#. PrePad + 2 drum Pro-Kem scale inhibitor + 1 and. ISIP 980#, closed at 770#. 403'. Ran pump and rods. Began pump testi	Completion or Recompletion Report and Log form.) g any proposed work. If well is directionally drilled, give lows: 1938', 56', 64', 82', 96', 98', 1', 06', 12', 40', 42', 47', 50', & 180,000 gals gel water + 6000# 100 ng.
11/5/96 RU Wedge WL. Ran Bond lo 2022', 73', 2108', 20', 42', 64', 88', 90 2385', for a total of 30 holes (.40" EH Acidize San Andres perfs 1938-2385' Frac'd perfs 1938-2385' w/1,000 gals mesh sand + 240,000# 20/40 Brady san	og from 2550' to surf. Perf'd w/1 SPF as follow; 2200', 12', 22', 34', 44', 78', 85', 2300', 02 HD Holes). w/2500 gals of 15% NeFe acid, ISIP 660#. PrePad + 2 drum Pro-Kem scale inhibitor + 1 and ISIP 980#, closed at 770#.	Completion or Recompletion Report and Log form) g any proposed work. If well is directionally drilled, lows: 1938', 56', 64', 82', 96', 9 1', 06', 12', 40', 42', 47', 50', &