| Submit 3 Copies to Appropriate District Office | State Of Nev Ene Minerals and Natura | w Mexico I Resources Departmen | t | Form C-103 Revised 1-1-89 |
|---|---|--|--------------------------------------|-------------------------------------|
| | JIL CONSERVAT | ION DIVISION | WELL API NO. | |
| DISTRICT P.O. Box 1980, Hobbs, NM | P.O. Box 88240 Santa Fe, New Mex | | 30-015-29368 | |
| DISTRICT II 811 South 1st St, Artesia, NM 88210 | | | 5. Indicate Type of Lease STATE | FEE X |
| DISTRICT III 1000 Rio Brazos Rd, Aztec, NM 87410 | | | 6. State Oil & Gas Leas | ie No. |
| SUNDRY NOTICES AND REPORTS ON WELLS | | | | |
| (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DETERMINE BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" | | | 7. Lease Name or Unit Agreement Name | |
| 1. Type of Well: | FORM C-101) FOR SUCH PROPOSALS.) | | | |
| OIL WELL GAS WELL X OTHER APR 0 3 155 | | | Chevron 32 State Com | |
| Nearburg Producing C 3. Address of Operator | ompany ONL | CON. DIV | #1 9. Pool name or Wildca | |
| P.O. Box 823085, Dall 4. Well Location | as. TX 75382-3085 | rist. I | | Draw, Morrow Gas |
| Unit Letter A | 1,090': Feet From The No | orth Line and | 990' Feet Fro | om The <u>East</u> Line |
| Section | 32 Township 17S | Range 27E | NMPM | Eddy County |
| 10. Elevation (Show whether DF, RKB, RT, GR, etc.) | | | | |
| 3,495' GR Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data | | | | |
| NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: | | | | |
| PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING | | | | |
| TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING | | | ING OPNS. PLU | G & ABANDONMENT |
| PULL OR ALTER CASING CASING TEST & CE | | | | |
| | | | ction Casing and Cement. | |
| 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting | | | | |
| any proposed work.) SEE RULE 1103. | | | | |
| Drilled to 9,570'. C&C hole. RU and run 242 jts 5-1/2" 17# N80 & K55 LTC casing. Set casing at 9,570'. C&C hole. Cement casing in two stages using 2,350 sx cement plus additives. Circ cement to surface on both stages. ND BOPE, set slips and cut-off 5-1/2" csg and install csg cap. Clean mud pits & release rig at 0830 hrs 03/26/97. | | | | |
| SIGNATURE TYPE OR PRINT NAME | mation above is true and complete to the be | st of my knowledge and ⁄lgr. of Drilling at | nd Production | DATE 04/02/97 PHONE 915/686-8235 |
| | AL SIGNED BY TIM W. GUM | | | |
| | CY A SUPERVISOR TITLE | | | DATE APR 4 1997 |
| CONDITIONS OF APPROVA | AL. IF ANY: | | | • |

CONDITIONS OF APPROVAL, IF ANY: