Form:3160-5 (June 1990)	UNITED ST DEPARTMENT OF BUREAU OF LAND	ATES 311 2.181 THE INTERIOR Are a Plan	ns. Division 3210-2835 FORM APPROVED 3210-2835 Government No. 1004-0136 Expires: March 31, 1993 5. Leese Designation and Seriel No.
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT-" for such proposals SUBMIT IN TRIPLICATE 1. Type of Well			NM-93469 6. If Indian, Allottee or Tribe Name rvoir.
			7. If Unit or CA, Agreement Designation
2. Name of Operator		^	8. Well Name and No. CV "23" Federal
Chi Operating, Inc. 3. Address and Telephone		WI CENTE OID	9. API Well No. #3
P.O. Box 1799 Midland, Texas 4. Location of Well (Footsge, Sec., T., R., M., or Survey Description) 660' FNL, 1980' FWL Section 23, T16S, R27E Eddto Carl Mark Sector			10. Field and Pool, or Exploratory Area Dog Canyon Grayburg //9. 11. County or Parish, State
Eddy Co., New Mex		DICATE NATURE OF NOTICE, REPOR	
	SUBMISSION		
Notice o	fintent	Abandonment Recompletion Plugging Back	Change of Plans Change of Plans New Construction Non-Routine Fracturing
Final Ab	andonment Natice	Casing Repair Altering Casing Other	Water Shut-Off Corversion to Injection Dispose Water (Nati: Report results of multiple completion on Wett Correlation an Accumplation Report, and Leg News.)
directionally drilled, give Spudded well 2/16/9 Notified BLM, Don E 1st plug : Td - 1410' 2nd plug: 561'- 0'.	subsurface locations and measured and the 8. Set 311' of 8 5/8"-24#. Circulat arly & Adam Solameh. Discussed	net details, and give pertinent dates, including estimate ue vertical depths for all markders and zones pertinent f ed 52 sks. 7 7/8" hole Td'd @ 1620' on 2/19 I plugging procedure as follows:	o this work.)"
directionally drilled, give Spudded well 2/16/9 Notified BLM, Don E 1st plug : Td - 1410' 2nd plug: 561'- 0'. Cement plugs, Class	Subsurface locations and measured and the based of the statement of the	ue vertical depths for all markdors and zones pertinent i ed 52 sks. 7 7/8" hole Td'd @ 1620' on 2/19 I plugging procedure as follows: k ke circulation with mud & spotted: sks. Penrose zone - 1516'-1534.	o this work.)"
directionally drilled, give Spudded well 2/16/9 Notified BLM, Don E 1st plug : Td - 1410' 2nd plug: 561'- 0'. Cement plugs, Class Plugging procedure:	 Subsurface locations and measured and the 18. Set 311' of 8 5/8"-24#. Circulat arity & Adam Solameh. Discussed ar	ue vertical depths for all markdors and zones pertinent i ed 52 sks. 7 7/8" hole Td'd @ 1620' on 2/19 I plugging procedure as follows: k ke circulation with mud & spotted: sks. Penrose zone - 1516'-1534.	b this work.)* B/98. Mudlog & logs indicate dry hole.
directionally drilled, give Spudded well 2/16/9 Notified BLM, Don E 1st plug : Td - 1410' 2nd plug: 561'- 0'. Cement plugs, Class Plugging procedure: Concluded operation	 subsurface locations and measured and the 18. Set 311' of 8 5/8"-24#. Circulat Early & Adam Solameh. Discussed on caliper. "C". Volumes based on caliper. TIH w/ drill pipe open ended. Brout 1st plug: 1620'-1410' - 50 2nd plug: 361' - 0' - 100 standing to the set of the	ue vertical depths for all marticlers and zones pertinent i ed 52 sks. 7 7/8" hole Td'd @ 1620' on 2/19 I plugging procedure as follows: k ke circulation with mud & spotted: 9 sks. Penrose zone - 1516'-1534. ks.	b this work.)* B/98. Mudlog & logs indicate dry hole.
directionally drilled, give Spudded well 2/16/9 Notified BLM, Don E 1st plug : Td - 1410' 2nd plug: 561'- 0'. Cement plugs, Class Plugging procedure: Concluded operation	 subsurface locations and measured and the 18. Set 311' of 8 5/8"-24#. Circulate farty & Adam Solameh. Discussed is "C". Volumes based on caliper. TiH w/ drill pipe open ended. Brown 1st plug: 1620'-1410' - 50 (2nd plug: 361' - 0' - 100 set of the set of the	ue vertical depths for all markdons and zones pertinent i ed 52 sks. 7 7/8" hole Td'd @ 1620' on 2/19 I plugging procedure as follows: ke circulation with mud & spotted: osks. Penrose zone - 1516'-1534. ks. $P_{OS}T = JD$ H - 17 - 98 PVH	2 Dete 02/20/98

Approved as to plugging of the well I	5on
Liability under bond is retained until	
surface restoration is completed.	