Form 3160-5 (June 1990)

UNIȚED STATES DEPARTMEN F THE INTERIOR BUREAU OF LAND MANAGEMENT

N.M.	Oil	Cc≃≒.	Divisio
d d C	4 44	1.	

01. S. 1st 3 10-2834 FORM APPROVED C 5 Form APP

Do not use this form for proposals to	CES AND REPORTS ON WELLS	5. Lease Designation and Serial No.	
Do not use this form for proposals to o Use "APPLICATION	OIF. NM-0557370 6. If Indian. Allottee or Tribe Name		
	MIT IN TRIPLICATE	0. If Indian. Allottee or Tribe Name	
1. Type of Well ☑ Oil ☐ Gas ☐ Other Well ☐ Well		7. If Unit or CA, Agreement Designation	
2. Name of Operator DEVON ENERGY CORPORATION (N	Well Name and No.		
3 Address and Telephone No.		1997 Eagle "34H" Federal #16	
20 NORTH BROADWAY, SUITE 1500	RECEI O, OKLAHOMA CITY, OKLAHOMA 73102 3405) @85336 14R	VED 9. API Well No. RTESIA 38-015-29654	
4. Location of Well (Footage, Sec., T., R., M., or Surv	vey Description)	Field and Pool, or Exploratory Area	
2310' FNL & 430' FEL of Section 34-1	7S-27E, Unit "H"	Red Lake (Q-G-SA) 11. County or Parish, State	
	्र शद्	Eddy County, NM	
CHECK APPROPRIATE BO	X(s) TO INDICATE NATURE OF NOTICE,	REPORT, OR OTHER DATA	
TYPE OF SUBMISSION	TYPE OF AC	TYPE OF ACTION	
Notice of Intent	Abandonment	Change of Plans	
Subsequent Report	Recompletion	New Construction	
	☐ Plugging Back☐ Casing Repair	Non-Routine Fracturing	
T result at 1 and 1	Casing Repair	Water Shut-Off	
Final Abandonment Notice	Altering Casing	Conversion to Injection	
Final Abandonment Notice	☐ Altering Casing ☐ Other Spud, Casing strings, TD	Conversion to Injection Dispose Water	
	Other Spud, Casing strings, TD	Dispose Water (Note: Report results of multiple completion on Well	
3. Describe Proposed or Completed Operations (Clearly state locations and measured and true vertical depths for all n Spudded this well on 9/24/97 at 14 ST&C csg, set at 1155°. Cemente Drld 7 7/8" hole and reached TD 2 Ran 60 jts 5 1/2" 15.5# J-55 LT& sxs of cmt.	Other Spud, Casing strings, TD all pertinent details, and give pertinent dates, including estimated date of start markers and zones pertinent to this work.)* 400 hrs and drld a 12 1/4" hole to 1156'. Or ed w/350 sx lite "C" + 200 sx Class "C". Cir 2700' on 9/29/97 at 1330 hrs. Schlumberge at C csg, set at 2700'. Cemented w/200 sx lite.	Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) In 9/26/97 ran 28 jts 8 5/8" 24# J-55 rc'd 38 sxs cmt. Per ran LDT/CNL/DLL/MSFL/GR logs. te "C" + 325 sx Class "C". Circ'd 21	
3. Describe Proposed or Completed Operations (Clearly state locations and measured and true vertical depths for all responses to the locations and measured and true vertical depths for all responses to the locations and measured and true vertical depths for all responses to the locations and measured and reached TD 2 ST&C csg, set at 1155°. Cemented TD 2 Ran 60 jts 5 1/2" 15.5# J-55 LT&C sxs of cmt. Released rig at 1600 hrs 9/30/97. Vertically that the foregoing is true and correct the locations and measured and true vertical depths for all responses to the locations and measured and true vertical depths for all responses to the locations and measured and true vertical depths for all responses to the locations and measured and true vertical depths for all responses to the locations and measured and true vertical depths for all responses to the locations and measured and true vertical depths for all responses to the locations and measured and true vertical depths for all responses to the locations and measured and true vertical depths for all responses to the locations and measured and true vertical depths for all responses to the locations and measured and true vertical depths for all responses to the locations and true vertical depths for all responses to the locations and true vertical depths for all responses to the locations and true vertical depths for all responses to the locations and true vertical depths for all responses to the locations and true vertical depths for all responses to the locations and true vertical depths for all responses to the locations and true vertical depths for all responses to the locations and true vertical depths for all responses to the locations and true vertical depths for all responses to the locations and true vertical depths for all responses to the locations and true vertical depths for all responses to the locations and true vertical depths for all responses to the locations and true vertical depths for all responses to the locations and true vertical depths for all r	all pertinent details, and give pertinent dates, including estimated date of start markers and zones pertinent to this work.)* 400 hrs and drld a 12 1/4" hole to 1156'. Or ed w/350 sx lite "C" + 200 sx Class "C". Cir 2700' on 9/29/97 at 1330 hrs. Schlumberge &C csg, set at 2700'. Cemented w/200 sx lite work. ACCEPTED FOR RECORD OCT 2 7 1987 OCT 2 7 1987	Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) ting any proposed work. If well is directionally drilled, give subsurfact of 19/26/97 ran 28 jts 8 5/8" 24# J-55 rc'd 38 sxs cmt. er ran LDT/CNL/DLL/MSFL/GR logs. te "C" + 325 sx Class "C". Circ'd 21	
3. Describe Proposed or Completed Operations (Clearly state locations and measured and true vertical depths for all n Spudded this well on 9/24/97 at 14 ST&C csg, set at 1155'. Cemented TD 2 Ran 60 jts 5 1/2" 15.5# J-55 LT& sxs of cmt. Released rig at 1600 hrs 9/30/97. Vertical corrections and correct the state of	all pertinent details, and give pertinent dates, including estimated date of start markers and zones pertinent to this work.)* 400 hrs and drld a 12 1/4" hole to 1156'. Or ed w/350 sx lite "C" + 200 sx Class "C". Cir 2700' on 9/29/97 at 1330 hrs. Schlumberge &C csg, set at 2700'. Cemented w/200 sx lite work.	Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) Iting any proposed work. If well is directionally drilled, give subsurfaction of the subsurfaction of	
3. Describe Proposed or Completed Operations (Clearly state locations and measured and true vertical depths for all n Spudded this well on 9/24/97 at 14 ST&C csg, set at 1155'. Cemente Drld 7 7/8" hole and reached TD 2 Ran 60 jts 5 1/2" 15.5# J-55 LT& sxs of cmt. Released rig at 1600 hrs 9/30/97. V	all pertinent details, and give pertinent dates, including estimated date of start markers and zones pertinent to this work.)* 400 hrs and drld a 12 1/4" hole to 1156'. Or ed w/350 sx lite "C" + 200 sx Class "C". Cir 2700' on 9/29/97 at 1330 hrs. Schlumberge &C csg, set at 2700'. Cemented w/200 sx lite work. ACCEPTED FOR RECORD OCT 2 7 1987 OCT 2 7 1987	Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) ting any proposed work. If well is directionally drilled, give subsurfact of the subsurfact o	

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to ny matter within its jurisdiction.

FROSWELL OFFICE