Form 3160-3 (December 1990)		STATES A			Form approved.		
*		OF THE INTERION NO MANAGEMENT	Interest and States and Stat	<u> Viviein</u>			
		and the	AHTESIA, NIN 88210	LC-026	FASTGMATION AND SERIAL NO. 874-F NAM, ALLOTTER OR TRIBE NAME		
	PLICATION FOR PERM		EPEN	ORAT INC	IAN, ALLOTTEE OR TRIBE MANE		
la TYPE OF WORK:	DRILL 🔀	DEEPEN			GREEKENT HAME		
	GAS WELL Other	SINGLE ZONB	MULTIPLE	A. TARK O	R LEASE MAKE, WELL NO.		
2 NAME OF OPERAT	OR DEVON ENERGY CORPO	DRATION (NEVADA)	1137	Evarts 3	3 Federal #1 223	35	
3. ADDRESS AND TE		E 1500, OKC, OK 73102 (409	5) 552-4511	9.AFI WE 30-015-	30044	-	
	L (Report location clearly and in a	ccordance with any State requirem		10. FIELD AND FOOL, OR WILDCAT Red Lake; Q-GB-SA			
At surface 1650'	FSL & 990' FWL of Section 33-T1	17S-R27E, Unit "L"	1122.22	11.SEC.,	T.,R.,M., OR BLOCK AND SURVE	Y OR AREA	
At top proposed prod.	zone (SAME)		\$192021222324 39	Section	33-T17S-27E		
	ND DIRECTION FROM NEAREST TOWN OF southeast of Artesia, NM	K FOAT OFFICE"	S INN 1998	Hody C	County New	STATE W Kico	
15.DISTANCE FROM PROPOR LOCATION TO MEAREST	SED	16.NO. OF ACRES IN LEASE	+ RECEIVED	18	17.NO. OF ACRES ASSIGN TO THIS WELL		
PROPERTY OR LEASE L1 (Also to nearest drig, unit line	•	200	RECEIVED CD · ARTESIA	e S	40		
18. DISTANCE FROM PROPOS TO MERREST WELL, DRI OR APPLIED FOR, CH 1	HED LOCATION* ILLING, COMPLETED,	19.PROPOSED DEPTH 2800'	1101	Ĩ	20. ROTARY OR CABLE TOO Rotary	LS*	
21. ELEVATIONS (Show whether		SWELL CONTROLLE	NALA TRO TROTACINA	1	APPROI. DATE WORK WILL STAR	17*	
G R 3539 '	₩2 <i>6.</i> 22	swel von invlei	d saater droin	Feb	oruary 10, 1998		
23.		PROPOSED CASING AND CEN					
SIZE OF HOLE	GRADE, SILE OF CASING	WEIGET PER POOT	SETTING DEPTE		QUANTITY OF CENEN	TT	
17 1/2" 12 1/4"	14" 8 5/8", J-55	Conductor 24 ppf	40' 1150'	Eee	Redimix		
7 7/8"	5 1/2", J-55	15.5 ppf	2800'	<u>E98</u>	350 sx Lite + 200 sx Class (150 sx Lite + 350 sx Class (
* Cement will be circula	ated to surface on all casing string	1	1		100 SA DIRC + 550 SA CIASS		
Devon Energy plans to	drill to 2800' +/- to test the San Au ndoned per Federal regulations.	ndres Formation for commercial	quantities of oil. If the San A il and gas regulations are out	andres is d	leemed non-commercial, the he following exhibits and atta	wellbore achments.	
Drilling Program Surface Use and Operat	8	The undersigned according to the operations conducted operations conduct	epts all applicable terms, con l on the leased land or portio	ditions, sti n thereo <u>f</u> ,	as described above.	g	
Exhibit #1 - Blowout Pr Choke May		Bond Coverage: Na	utionwide	Ģ	E Por	led ID]	
Exhibit #2 - Location ar					H NIN	IAPT	
Exhibit #3 - Planned Ac Exhibit #4 - Wells With		Bond Coverage: Nationwide BLM Bond File No.: CO-1104 APPROVAL SUBJECT TO GENERAL REQUIREMENTS AND				2. 00-	
Exhibit wo - I founded I fail						30.18	
	ign Parameters and Factors		STIPULATIONS	-			
Exhibit #8 - H2S Operat	ing Plan	ATTACHE	Ð	- (12. F A	cs)	
proposal is to drill or de	SCRIBE PROPOSED PROGRAM repen directionally, give pertinent	A: If proposal is to deepen, give d data on subsurface locations and	ata on present productive zo measured and true vertical	ne and pro depths. G	posed new productive zone.	5/9 8 (f am, if	
any. 24.			· · · · · · · · · · · · · · · · · · ·				
þ		E I. RID	TTROSS, JR.				
SIGNED	2. Butross fr	TITLE DISTRIC		ſĽ	_12/17/ <u>77</u>		
*(This space for Feder	ral or State office use)						
			APPROVAL DATE				
Application approval does n CONDITIONS OF APP	ot warrant or certify that the applicant ROVAL, IF ANY:	holds legal or equitable title to those r \triangle	ights in the subject lease which w	ould entitle	the applicant to conduct operatio	ns thereon.	

APPROVED BY	(ORIG. SGE).) ARMANDO	A.	LOPEZ
-------------	------------	-------------	----	-------

|--|

DATE	 20	-98

See Instructions On Reverse Side

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

DISTRICT I P.O. Box 1980, Hobbs, NM 88240

DISTRICT II P.O. Drawer DD, Artesia, NM 68210

DISTRICT III 1000 Rio Brazos Rd., Artec, NM 57410 State of New Mexico

HIBIT #

Energy, Minerals and Natural Resources Department

Revised Pebruary 10, 1994 Instruction on back Submit to Appropriate District Office State Lease - 4 Copies Fee Lease - 3 Copies

2

OIL CONSERVATION DIVISION P.O. Box 2088 Santa Fe, New Mexico 87504-2088

WELL LOCATION AND ACREAGE DEDICATION PLAT

C AMENDED REPORT

Form C-102

API Number Pool Code Pool Name Red Lake (Q-GB-SA) **Property** Code **Property** Name Well Number EVARTS "33" FEDERAL 1 OGRID No. **Operator** Name Elevation DEVON ENERGY CORPORATION 3539' Surface Location UL or lot No. Lot Idn Feet from the Section Township Range North/South line East/West line Feet from the County 17 S 33 27 E 1650 SOUTH L 990 WEST EDDY Bottom Hole Location If Different From Surface UL or lot No. Section Range Lot Idn Feet from the North/South line Township Feet from the East/West line County Dedicated Acres Joint or Infill **Consolidation** Code Order No. NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION **OPERATOR CERTIFICATION** I hereby certify the the information contained herein is true and complete to the best of my knowledge and belief. E. L. Buttross, Jr. Printed Name District Engineer Title 12/16/97 Date - SURVEYOR CERTIFICATION I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervison, and that the same is true and correct to the best of my belief. 3537.8 November 03, 1997 Date Servered, JON, Signature & Seal of S 3539.8 Professional Surveyor S s POFESSIONAL LIN 7977 DASIN SURVEY S



Attachment to Exhibit #1 NOTES REGARDING BLOWOUT PREVENTORS Evarts 33 Federal #1 Eddy County, New Mexico

- 1. Drilling nipple will be constructed so it can be removed mechanically without the aid of a welder. The minimum internal diameter will equal BOP bore.
- 2. Wear ring will be properly installed in head.
- 3. Blowout preventor and all associated fittings will be in operable condition and tested to 1000 psi with the right pump.
- 4. All fittings will be flanged.
- 5. A full bore safety valve with proper thread connections will be available on the rotary rig floor at all times.
- 6. All choke lines will be anchored to prevent movement.
- 7. All BOP equipment will be equal to or larger in bore than the internal diameter of the last casing string.
- 8. Will maintain a Kelly cock attached to the Kelly.
- 9. Hand wheels and wrenches will be properly installed and tested for safe operation.
- 10. All BOP equipment will meet API standards and include a minimum 40 gallon accumulator having two independent means of power to initiate closing operation.