

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Engr., Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-015-30166
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. V-4129
7. Lease Name or Unit Agreement Name Crow ASM State Com
8. Well No. 1
9. Pool name or Wildcat POW Morrow

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER
2. Name of Operator YATES PETROLEUM CORPORATION
3. Address of Operator 105 South 4th St., Artesia, NM 88210
4. Well Location Unit Letter N : 660 Feet From The South Line and 2310 Feet From The West Line Section 32 Township 16S Range 28E NMPM Eddy County
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3621' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: Intermediate casing & cement <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 2005'. Reached TD at 6:00 AM 5-31-98. Ran 45 joints of 8-5/8" 24# 8rd ST&C (2019.17') of casing set at 2012'. 1-regular guide shoe set at 2012'. Float collar set at 1974'. Cemented with 650 sacks BJ Lite, 5#/sack salt, 5#/sack gilsonite and 1/4#/sack celloflake (yield 2.00, weight 12.4). Tailed in with 200 sacks "C" and 2% CaCl2 (yield 1.34, weight 14.8). PD 2:00 PM 5-31-98. Bumped plug to 1400 psi, OK. Circulated 222 sacks. WOC. Nipped up and tested to 3000 psi for 10 minutes, OK. Drilled out at 10:30 AM 6-1-98. WOC 19 hours and 30 minutes. Reduced hole to 7-7/8". Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Operations Technician DATE June 8, 1998

TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-1471

(This space for State Use)

APPROVED BY Jim W. Green TITLE District Supervisor DATE 6-11-98

CONDITIONS OF APPROVAL, IF ANY: