

Page 2

WELL: WALLACE STATE COM NO. 1, 5-1/2" HEAVY

MEASURED		INCLINATION		AZIMUTH		BORE HOLE BEARING		DOGLEG SEVERITY deg./ 100 ft.	VERTICAL		CLOSURE		HORIZONTAL	
DEPTH feet	deg.	deg.	deg.	min.	deg.	DEPTH feet	DIST. feet		AZIMUTH deg.	DIST. feet	AZIMUTH deg.	DIST. feet	AZIMUTH deg.	
2100.0	1.27	205.41	S 25 24 W		.20	2099.1	47.9	172.4	47.44	S	6.29	E		
2200.0	1.33	199.25	S 19 15 W		.15	2199.1	49.8	173.7	49.54	S	5.43	E		
2300.0	1.17	210.97	S 30 58 W		.30	2299.0	51.7	175.0	51.51	S	4.52	E		
2400.0	1.37	210.32	S 30 19 W		.20	2399.0	53.5	176.4	53.42	S	3.39	E		
2500.0	1.16	213.23	S 33 14 W		.22	2499.0	55.3	177.7	55.30	S	2.24	E		
2600.0	.99	219.09	S 39 6 W		.20	2599.0	56.8	178.9	56.81	S	1.14	E		
2700.0	1.08	212.35	S 32 21 W		.15	2699.0	58.3	179.9	58.28	S	.09	E		
2800.0	1.13	217.94	S 37 56 W		.12	2798.9	59.9	181.0	59.85	S	1.02	W		
2900.0	.99	214.20	S 34 12 W		.16	2898.9	61.4	182.0	61.35	S	2.11	W		
3000.0	.99	211.26	S 31 15 W		.05	2998.9	62.9	182.8	62.80	S	3.05	W		
3100.0	1.11	208.36	S 28 21 W		.13	3098.9	64.5	183.5	64.39	S	3.96	W		
3200.0	1.08	209.93	S 29 56 W		.04	3198.9	66.2	184.2	66.05	S	4.88	W		
3300.0	1.07	218.27	S 38 16 W		.16	3298.9	67.9	185.0	67.60	S	5.93	W		
3400.0	.88	201.33	S 21 20 W		.34	3398.8	69.4	185.6	69.05	S	6.79	W		
3500.0	.95	234.24	S 54 14 W		.52	3498.8	70.7	186.3	70.24	S	7.74	W		
3600.0	1.04	231.81	S 51 48 W		.11	3598.8	71.9	187.3	71.29	S	9.12	W		
3700.0	.91	234.75	S 54 45 W		.14	3698.8	73.1	188.3	72.31	S	10.49	W		
3800.0	1.08	237.64	S 57 38 W		.17	3798.8	74.2	189.2	73.27	S	11.93	W		
3900.0	.91	241.14	S 61 8 W		.18	3898.8	75.4	190.3	74.16	S	13.42	W		
4000.0	.85	243.69	S 63 41 W		.07	3998.8	76.3	191.2	74.87	S	14.78	W		
4100.0	.84	240.86	S 60 51 W		.04	4098.8	77.3	192.0	75.56	S	16.09	W		
4200.0	.87	252.25	S 72 15 W		.17	4198.7	78.1	192.9	76.15	S	17.45	W		
4300.0	.79	253.18	S 73 11 W		.08	4298.7	78.9	193.8	76.58	S	18.83	W		
4400.0	.95	249.59	S 69 35 W		.17	4398.7	79.7	194.7	77.07	S	20.26	W		
4500.0	.69	262.15	S 82 9 W		.32	4498.7	80.4	195.6	77.44	S	21.63	W		