

Form 4
(Oct. 1990)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE

W. Grand Avenue
Tesia, NM 88210

(See instructions on
reverse side)

WELL COMPLETION OR RECOMPLETION REPORT AND LOG*

1a. TYPE OF WELL: OIL WELL ☒ GAS WELL ☐ DRY ☐ Other ☐

b. TYPE OF COMPLETION: NEW WELL ☐ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF. RESVR ☒ Other ☐

2. NAME OF OPERATOR

DEVON ENERGY CORPORATION (NEVADA)

3. ADDRESS AND TELEPHONE NO.

20 N. BROADWAY, SUITE 1500, OKC, OK 73102-8260 (405) 235-3613

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)*

At surface 2100' FSL & 840' FEL

At top prod. interval reported below

At total depth

5. LEASE DESIGNATION AND SERIAL NO.
LC-057798

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME, WELL NO.
Logan 35 Federal #2

9. API WELL NO.
30-015-30436

10. FIELD AND POOL, OR WILDCAT
Red Lake; (Q-GB-SA) & Glorieta-Yeso, NE

11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA
Sec 35, T-17-S, R-27-E

14. PERMIT NO.

DATE ISSUED

12. COUNTY OR PARISH
Eddy County

13. STATE
New Mexico

15. DATE SPUDDED 3/7/00 16. DATE T.D. REACHED 3/24/00 17. DATE COMPL. (Ready to prod.) 6/7/01 18. ELEVATIONS (DF, RKB, RT, GR, ETC.)* 3635' GR 19. ELEV. CASINGHEAD

20. TOTAL DEPTH, MD & TVD 3752' 21. PLUG, BACK T.D., MD & TVD 3618' 22. IF MULTIPLE COMPL., HOW MANY* 23. INTERVALS DRILLED BY 24. ROTARY TOOLS X 25. CABLE TOOLS

24. PRODUCING INTERVAL(S), OF THIS COMPLETION-TOP, BOTTOM, NAME (MD AND TVD)*
Yeso 3176' - 3454'
Upper San Andres 2032' - 2456'
Lower San Andres 2742' - 2861'
25. WAS DIRECTIONAL SURVEY MADE No

26. TYPE ELECTRIC AND OTHER LOGS RUN 27. WAS WELL CORED No

28. CASING RECORD (Report all strings set in well)

CASING SIZE/GRADE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	TOP OF CEMENT, CEMENTING RECORD	AMOUNT PULLED
14"	Conductor	40'	17 1/2"	Redimix	
8 5/8" K-55	24	1150'	12 1/4"	350 sx lite + 200 sx Class C	
5 1/2" J-55	15.5	3400'	7 7/8"	250 sx lite + 250 sx Class C	

29. LINER RECORD 30. TUBING RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
					2 7/8"	3457'	

31. PERFORATION RECORD (Interval, size and number)
Yeso 3176' - 3454'
Upper San Andres 2032' - 2454' 30 holes
Lower San Andres 2742' - 2861' - 17 holes
32. ACID SHOT, FRACTURE, CEMENT SQUEEZE, ETC.
DEPTH INTERVAL (MD) AMOUNT AND KIND OF MATERIAL USED
2032' - 2456' 2500 Gal 15% NeFe Acid
2742' - 2861' 1500 Gal 15% NeFe Acid
2032' - 2861' 214,000 gal Fresh & linear gel wtr + 106,750# 20/40 Brady SD + 24500 # 16/30 CRC SD

33.* PRODUCTION

DATE FIRST PRODUCTION 6/7/01 PRODUCTIONS METHOD 1 (Flowing, gas lift, pumping—size and type of pump) Pumping (2" X 2 1/2" X 16" RWTC) WELL STATUS (Producing or shut-in) Producing

DATE OF TEST 6/26/01 HOURS TESTED 24 CHOKER SIZE PROD'N FOR TEST PERIOD OIL-BBL. 106 GAS-MCF. 130 WATER-BBL. 351 GAS-OIL RATIO 1.226/1

FLOW. TUBING PRESS. CASING PRESSURE CALCULATED 24-HOUR RATE OIL-BBL. 106 GAS-MCF. 130 WATER-BBL. 351 OIL GRAVITY-API (CORR.) 42

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.) Sold TEST WITNESSED BY Danny Hokett

35. LIST OF ATTACHMENTS

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED Karen Cottom

KAREN COTTOM
TITLE ENGINEERING TECHNICIAN

DATE October 2, 2001

*(See Instructions and Spaces for Additional Data on Reverse Side)

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

RECEIVED

2004 OCT -9 AM 9:13

SUPREMACY COURT
BIRMINGHAM OFFICE

OUR VISION

NAME	TOP	
	MEAS. DEPTH	TRUE VERT. DEPTH
Bosnia	752'	
Queens	942'	
Grayburg	1362'	
Premier	1656'	
San Andres	1704'	
Glorieta	3050'	
Yaso	3136'	

RECEIVED

2001 OCT -9 AM 9:13

BUREAU OF LAND MANAGEMENT
ROSWELL OFFICE