

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Bonos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO.	30-015-30446
5. Indicate Type of Lease	STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.	B-8318-128
7. Lease Name or Unit Agreement Name	
OXY Chopsticks State	
23824	
8. Well No.	1
9. Pool name or Wildcat	
Undsg. Logan Draw Morrow 80400	

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	2. Name of Operator OXY USA Inc.	16696
3. Address of Operator P.O. Box 50250 Midland, TX 79710-0250	9. Pool name or Wildcat Undsg. Logan Draw Morrow 80400	
4. Well Location Unit Letter F : 1750 Feet From The North Line and 1980 Feet From The West Line Section 24 Township 17S Range 27E NMPM Eddy County		
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3483'		

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER: <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

SEE OTHER SIDE

NEW: TD-9600' - 8-5/8" casing @ 1500' w/ 725sx  
4-1/2" casing @ 9600' w/ 705sx

WAS: TD-9800' - 8-5/8" casing @ 1800' w/ 775sx  
4-1/2" casing @ 9800' w/ 730sx



I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE David Stewart TITLE Regulatory Analyst DATE 5/27/89  
TYPE OR PRINT NAME David Stewart TELEPHONE NO. 9156855717

(This space for State Use)

APPROVED BY Jim W. Green TITLE District Supervisor DATE 6-3-89  
CONDITIONS OF APPROVAL, IF ANY:

ATTACHMENT C-101  
OXY USA Inc.  
OXY Chopstick State #1  
SEC 24 T17S R27E  
Eddy County, NM

PROPOSED TD: 9600' TVD

BOP PROGRAM: 0' - 1500' 20" X 40' Conductor pipe with 13-3/8" rotating head bolted on. To be used as divertor only.

1500'-9800' 8-5/8 5M blind and pipe rams with 5M annular preventer and rotating head below 6000'.

CASING: 8-5/8" 32# K55 ST&C casing @ 1500'. 12-1/4" hole.

4-1/2" 11.6# N80 LT&C casing @ 9600'. 7-7/8" hole.

CEMENT: Surface - Circulate cement with 525sx 35:65 POZ/C with 6% Bentonite + .005% Static Free + .005gps FP-6L + 2% CaCl<sub>2</sub> + 0.25#/sx Cello Flake + 5#/sx Gilsonite followed by 200sx Cl C with 2% CaCl<sub>2</sub> + .005#/sx Static Free + .005gps FP-6L.

Production - Cement with 630sx 15:61:11 POZ/C/CSE with .005#/sx Static Free + 8#/sx Gilsonite + .5% FL-25 + .5% FL-52 + .005gps FP-6L followed by 75sx Cl C with .005#/sx Static Free + .7% FL-25 + .005gps FP-6L.

Estimated top of cement is 6000 .

Cement volumes may be adjusted to hole caliper.

MUD: 0' - 1500' FW/gel/lime. Lime for pH control (9-10). Paper for seepage. Wt. 8.6-9.2ppg, vis 28-34sec.

1500'-6000' Fresh water. Lime for pH control (9-9.5). Paper for seepage. Wt. 8.3-8.5ppg, vis 28-29sec

6000'-8700' Cut brine. Lime for pH control (10-10.5). Wt. 9.6-10.0ppg, vis 28-29sec

8700'-9800' Mud up with a Duo Vis/Flo Trol system Wt. 9.6-10.0ppg, vis 34-38sec WL 8cc.