

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

YATES PETROLEUM CORPORATION (505) 748-1471

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

660' FSL & 660' FEL of Section 30-T17S-R27E (Unit P, SESE)

5. Lease Designation and Serial No.

LC-026874F

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Dosequis ASQ Fed Com #1

9. API Well No.

30-015-30464

10. Field and Pool, or Exploratory Area

Wildcat Morrow

11. County or Parish, State

Eddy Co., NM

12 CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Spud, conductor, resume drilling, surface casing & cement
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded a 20" hole with rat hole machine at 2:15 PM 2-19-99. Set 40' of 16" conductor pipe. Cemented to surface. NOTE: Notified Cathy Queen w/BLM-Carlsbad of spud. Resumed drilling a 12-1/4" hole with rotary tools at 7:15 PM 2-21-99. NOTE: Notified Jim Amos w/BLM-Carlsbad of resume drilling.

TD 1430'. Reached TD at 2:30 PM 2-23-99. Ran 32 joints of 8-5/8" 24# J-55 (1433.39') of casing set at 1430'. 1-Texas Pattern notched guide shoe set at 1430'. Float collar set at 1388'. Cemented with 100 sacks Class H, 10% A-10B, 10#/sack gilsonite, 1% CaCl2 and 1/4#/sack celloflake (yield 1.5, weight 14.6) and 850 sacks BJ Lite C, 6% gel, 5#/sack salt, 1/4#/sack celloflake and 5#/sack gilsonite (yield 2.03, weight 12.52). Tailed in with 200 sacks Class C and 2% CaCl2 (yield 1.34, weight 14.8). PD 9:30 PM 2-23-99. Bumped plug to 1200 psi, OK. Circulated 198 sacks. WOC. Nippled up and tested to 1000# for 15 minutes, OK. Drilled out at 11:45 PM 2-24-99. WOC 14 hours and 15 minutes. Reduced hole to 7-7/8". Resumed drilling.

14. I hereby certify that the foregoing is true and correct

Signed

Title Operations Technician

Date March 1, 1999

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any: