

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

YATES PETROLEUM CORPORATION (505) 748-1471

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FSL & 990' FWL of Section 14-T17S-R27E (Unit L, NWSW)

5. Lease Designation and Serial No.

NM-99028

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Duke ARP Federal Com #1

9. API Well No.

30-015-30476

10. Field and Pool, or Exploratory Area

Undesignated Morrow

11. County or Parish, State

Eddy Co., NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Spud, conductor, resume drilling, surface csg & cmt



☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded a 20" hole with rat hole machine at 4:00 PM 11-30-98. Set 40' of 16" conductor pipe and cemented to surface. NOTE: Notified Gene Hunt w/BLM-Carlsbad of spud. Resumed drilling a 12-1/4" hole with rotary tools at 2:45 PM 12-2-98.

TD 1605'. Reached TD at 8:15 PM 12-4-98. Ran 36 joints of 8-5/8" 24# J-55 (1612.23') of casing set at 1605'. 1-Texas Pattern notched guide shoe set at 1605'. Float collar set at 1560'. Cemented with 800 sacks Class C (65-35-6), 5#/sack salt, 5#/sack gilsonite and 1/2#/sack celloflake (yield 2.03, weight 12.5). Tailed in with 200 sacks Class C and 2% CaCl2 (yield 1.34, weight 14.8). PD 4:30 AM 12-5-98. Bumped plug to 950 psi, OK. Circulate 153 sacks. WOC. Nipped up and tested to 1000 psi for 15 minutes, OK. Cut off and welded on flow nipple. Drilled out at 10:45 AM 12-6-98. WOC 30 hours and 15 minutes. Reduced hole to 7-7/8". Resumed drilling.



14. I hereby certify that the foregoing is true and correct

Signed Rusty Allen

Title Operations Technician

Date Dec. 7, 1998

(This space for Federal or State office use)

Approved by _____

Title _____

Date _____

Conditions of approval, if any: