

Submit 3 copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

DISTRICT I

P.O. Box 1980, Hobbs, NM 88240

DISTRICT II

P.O. Drawer DD, Artesia, NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088

Santa Fe, New Mexico 87504 -2088

WELL API NO.

30-015-30562

5. Indicate Type of Lease

STATE ☒

FEE ☐

6. State Oil & Gas Lease No.

2029

7. Lease Name or Unit Agreement Name

Mule Train 16

State Com

8. Well No.

1

9. Pool name or Wildcat

Red Lake Morrow NE

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL

Well ☐

GAS

Well ☒

OTHER

2. Name of Operator

Yates Drilling Company

3. Address of Operator

105 S. 4th Street, Artesia, NM 88210

4. Well Location

Unit Letter G : 1500 Feet From The North Line and 1650 Feet From The East Line

Section 16

Township 17S

Range 28E

NMPM

Eddy

County

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

☐

PULL OR ALTER CASING ☐

OTHER: ☐

☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☒

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

11-5-99 TD 10,250'. Reached TD at 11:30 PM, 11-2-99. Ran 245 jts. casing, set at 10,250', as follows:

57 jts. 5 1/2" 17# N-80 8R LT&C (2342.77')

41 jts. 5 1/2" 17# J-55 8R LT&C (1705.87')

110 jts. 5 1/2" 15.50# J-55 8R LT&C (4686.96')

27 jts. 5 1/2" 17# J-55 8R LT&C (1124.45')

10 jts. 5 1/2" 17# L-80 8R LT&C (412.03')

Davis Lynch float shoe set at 10,250'. Davis Lynch float collar set at 10,210.12'. Cemented with 800 sxs. Super Modified C with 8# gilsonite + .522#/sx FL-25 + .522#/sx FL-52 (yld 1.61, wt 13.10). Tailed in with 75 sxs Class "C" with .7% FL-52 (yld 1.33, wt 14.8). PD at 6:15 PM, 11-2-99. Bumped plug to 2400 psi for 3 mins. Float and casing held okay. Rig released at 11:15 PM, 11-4-99. Waiting on completion unit.



I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Karen J. Leishman TITLE Engineering Technician

DATE 12-10-99

TYPE OR PRINT NAME Karen J. Leishman

TELEPHONE NO. 505-748-4500

(This space for State Use)

APPROVED BY Jim W. Bann

TITLE District Supervisor

DATE 12-14-99

CONDITIONS OF APPROVAL, IF ANY: