

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.	30-015-30563
5. Indicate Type of Lease	STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.	VA-1551
7. Lease Name or Unit Agreement Name	
Riverside ASS State Com	
8. Well No.	1
9. Pool name or Wildcat	Crow Flats Morrow
10. Elevation (Show whether DF, RKB, RT, GR, etc.)	
3368' GR	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:	OIL WELL <input type="checkbox"/>	GAS WELL <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>
2. Name of Operator	YATES PETROLEUM CORPORATION		
3. Address of Operator	105 South 4th St., Artesia, NM 88210		

4. Well Location	Unit Letter <u>I</u> : <u>1650</u> Feet From The <u>South</u> Line and <u>660</u> Feet From The <u>East</u> Line		
Section <u>8</u>	Township <u>17S</u>	Range <u>27E</u>	NMPM <u>Eddy</u> County
10. Elevation (Show whether DF, RKB, RT, GR, etc.)			
3368' GR			

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 20" hole with rat hole machine at 9:30 AM 2-25-99. Set 40' of 16" conductor pipe. Cemented to surface. NOTE: Notified Gary w/OCD-Artesia of spud. Resumed drilling a 12-1/4" hole with rotary tools at 10:00 PM 2-26-99.

TD 1432'. Ran 32 joints of 8-5/8" 24# J-55 8rd ST&C (1436.33') of casing set at 1432'. 1-Texas Pattern notched guide shoe set at 1432'. Float collar set at 1384'. Cemented with 600 sacks Halliburton Lite Premium Plus, 1/4#/sack flocele, 5#/sack gilsonite and 2% CaCl2 (yield 2.01, weight 12.6). Tailed in with 200 sacks Premium Plus with 2% CaCl2 (yield 1.32, weight 14.8). PD 11:30 PM 2-28-99. Bumped plug to 725 psi, OK. Circulated 78 sacks. WOC. Nippled up and tested to 3000 psi for 30 minutes, OK. Drilled out at 6:00 PM 3-1-99. WOC 18 hours and 30 minutes. Reduced hole to 7-7/8". Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Operations Technician DATE March 3, 1999

TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-1471

(This space for State Use)

APPROVED BY Jim W. Green TITLE District Supervisor DATE 3-11-99

CONDITIONS OF APPROVAL, IF ANY: