

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.
30-015-30659

5. Indicate Type of Lease
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.
NM-98809

7. Lease Name or Unit Agreement Name
Concho ACT State Com

8. Well No.
1

9. Pool name or Wildcat
Crow Flats Morrow

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
3362' GR

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☐ GAS WELL ☒ OTHER ☐

2. Name of Operator
YATES PETROLEUM CORPORATION

3. Address of Operator
105 South 4th St., Artesia, NM 88210

4. Well Location
Unit Letter H : 1650 Feet From The North Line and 660 Feet From The East Line
Section 8 Township 17S Range 27E NMPM Eddy County

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: Spud & surface casing ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 20" hole with rat hole machine at 10:45 AM 6-2-99. Set 40' of 16" conductor pipe. Cemented to surface. NOTE: Notified Mary Ann w/OCD-Artesia of spud. Resumed drilling a 12-1/4" hole with rotary tools at 7:00 AM 6-4-99.

TD 1407'. Reached TD at 11:30 PM 6-5-99. Ran 32 joints of 8-5/8" 24# J-55 8rd ST&C (1410.87') of casing set at 1407'. 1-Texas Pattern notched guide shoe set at 1407'. Insert float set at 1363'. Cemented with 650 sacks BJ Lite, 1/4#/sack celloseal, 5#/sack gilsonite and 5#/sack salt (yield 2.04, weight 12.4). Tailed in with 200 sacks "C" with 2% CaCl2 (yield 1.34, weight 14.8). PD 11:45 AM 6-6-99. Bumped plug to 300 psi, OK. Circulated 164 sacks. WOC. Nippled up and tested to 3000 psi for 10 minutes, OK. Drilled out at 9:15 PM 6-7-99. WOC 33 hours and 30 minutes. Reduced hole to 7-7/8". Resumed drilling. NOTE: Notified Gary Robinson w/OCD-Artesia of cementing.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Operations Technician DATE June 9, 1999
TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-1471

(This space for State Use)

APPROVED BY Jim W. Gump TITLE District Supervisor DATE 6-22-99

CONDITIONS OF APPROVAL, IF ANY: