

Measured Depth FT	Incl Angle Deg	Drift Direction Deg	True Vertical Depth	N-S FT	E-W FT	Vertical Section FT	CLOSURE		Dogleg Severity Deg/100
							Distance FT	Direction Deg	
7339.00	3.75	S34.00W	7332.29	-171.65	-44.70	174.73	177.37	S14.60W	2.95
7432.00	4.25	S37.00W	7425.06	-176.92	-48.47	180.29	183.44	S15.32W	.58
7538.00	5.25	S33.00W	7530.70	-184.12	-53.48	187.88	191.73	S16.19W	.99
7633.00	4.75	S34.00W	7625.34	-191.03	-58.04	195.14	199.65	S16.90W	.53
7755.00	5.75	S39.00W	7746.82	-199.97	-64.71	204.59	210.18	S17.93W	.90

M.W.D. Surveys

7828.00	7.10	S29.30W	7819.37	-206.74	-69.22	211.71	218.03	S18.51W	2.37
7891.00	8.00	S15.60W	7881.83	-214.36	-72.31	219.56	226.23	S18.64W	3.18
7953.00	8.20	S5.00W	7943.21	-222.92	-73.85	228.22	234.84	S18.33W	2.43
8016.00	8.60	S9.40E	8005.54	-232.05	-73.48	237.28	243.40	S17.57W	3.39
8079.00	8.30	S27.40E	8067.87	-240.73	-70.61	245.70	250.88	S16.35W	4.21
8141.00	7.70	S35.10E	8129.27	-248.10	-66.16	252.68	256.78	S14.93W	1.98
8250.00	7.50	S32.00E	8237.31	-260.11	-58.20	264.00	266.54	S12.61W	.42
8345.00	6.50	S31.00E	8331.60	-269.98	-52.14	273.34	274.97	S10.93W	1.06
8443.00	6.75	S30.00E	8428.95	-279.72	-46.40	282.58	283.54	S9.42W	.28
8465.00	6.30	S32.10E	8450.80	-281.86	-45.12	284.61	285.45	S9.09W	2.31
8511.00	6.40	S31.70E	8496.52	-286.18	-42.43	288.69	289.31	S8.43W	.24
8573.00	5.80	S32.40E	8558.17	-291.77	-38.93	293.97	294.35	S7.60W	.98
8636.00	5.00	S38.60E	8620.89	-296.60	-35.52	298.51	298.72	S6.83W	1.57
8698.00	4.70	S46.90E	8682.67	-300.45	-31.97	302.06	302.15	S6.07W	1.23
8762.00	3.90	S59.50E	8746.49	-303.35	-28.18	304.63	304.65	S5.31W	1.93
8822.00	3.60	S57.60E	8808.36	-305.39	-24.84	306.40	306.40	S4.65W	.54
8884.00	2.60	S53.00E	8868.27	-307.28	-22.07	308.06	308.07	S4.11W	1.66
8949.00	1.90	S36.40E	8933.22	-309.03	-20.25	309.66	309.70	S3.75W	1.46
--Projection to Bit--									
9000.00	1.35	S23.38E	8984.20	-310.27	-19.51	310.82	310.88	S3.60W	1.29