

## FIELD REPORT FOR CEMENTING OF WELLS

OIL CONSERVATION DIVISION

Expires 6/1/2000

30-015-30660

Operator <u>Nearburg Prod. Co.</u>		Lease <u>Hagaman 34</u>		Well # <u>1</u>	
Location of Well	Unit <u>St. 1</u>	Section <u>3</u>	Township <u>17</u>	Range <u>25</u>	County <u>Eddy</u>
Drilling Contractor <u>Patterson</u>			Type of Equipment <u>Rotary</u>		

Call OCD at Spud

## APPROVED CASING PROGRAM

\* Witness 8 5/8

Min. WOC 18 Hours

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
17 1/2	13 3/8	48 #		400'	500 Circ
12 1/4	* 8 5/8	24 #		1200'	775 Circ
7 7/8	5 1/2	17 # + 20 #		8100'	950

## Casing Data:

Surface \_\_\_\_\_ joints of \_\_\_\_\_ inch \_\_\_\_\_ # Grade \_\_\_\_\_  
 (Approved) (Rejected) \_\_\_\_\_

Inspected by \_\_\_\_\_ date \_\_\_\_\_

## Cementing Program

Size of hole \_\_\_\_\_ Size of Casing \_\_\_\_\_ Sacks cement required \_\_\_\_\_

Type of Shoe used \_\_\_\_\_ Float collar used \_\_\_\_\_ Btm 3 jts welded \_\_\_\_\_

TD of hole \_\_\_\_\_ Set \_\_\_\_\_ Feet of \_\_\_\_\_ Inch \_\_\_\_\_ # Grade \_\_\_\_\_

New-used csg. @ \_\_\_\_\_ with \_\_\_\_\_ sacks neat cement around shoe  
 + \_\_\_\_\_ sack \_\_\_\_\_ additives \_\_\_\_\_

Plug down @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_

Cement circulated \_\_\_\_\_ No. of Sacks \_\_\_\_\_

Cemented by \_\_\_\_\_ Witnessed by \_\_\_\_\_

Temp. Survey ran @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_ top cement @ \_\_\_\_\_

Casing test @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_

Method Used \_\_\_\_\_ Witnessed by \_\_\_\_\_

Checked for shut off @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_

Method used \_\_\_\_\_ Witnessed by \_\_\_\_\_

Remarks: 6-10-79-299-2135 714' K-55 1218' 1218' 1218'

2nd 1218' 1218' 1218' 1218' 1218' 1218' 1218' 1218' 1218' 1218'

1218' 1218' 1218' 1218' 1218' 1218' 1218' 1218' 1218' 1218'

1218' 1218' 1218' 1218' 1218' 1218' 1218' 1218' 1218' 1218'

1218' 1218' 1218' 1218' 1218' 1218' 1218' 1218' 1218' 1218'