

N.M. Oil Cons. Division
811 S. 1st St.
Artesia, NM 88210-2834

C/SF

Form 3160-5
(June 1990)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

YATES PETROLEUM CORPORATION

(505) 748-1000

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1780' FNL & 990' FWL of Section 33-T16S-R27E (Unit E, SWNW)

5. Lease Designation and Serial No.

NM-93190

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Lucky Lobo ASX Fed Com #1

9. API Well No.

30-015-30667

10. Field and Pool, or Exploratory Area

Undesignated Morrow

11. County or Parish, State

Eddy Co., NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Spud & surface casing
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Spudded a 20" hole with rat hole machine at 3:00 PM 6-29-99. Set 40' of 16" conductor pipe. Cemented to surface. NOTE: Notified Jim Amos w/BLM-Carlsbad of spud. Resumed drilling a 12-1/4" hole with rotary tools at 12:00 noon 7-1-99.

TD 1340'. Reached TD at 4:15 AM 7-3-99. Ran 30 joints of 8-5/8" 24# J-55 (1344.91') of casing set at 1340'. 1-Texas Pattern notched guide shoe set at 1340'. Float collar set at 1295'. Cemented with 650 sacks Class C (65-35-6), 5#/sack salt, 1/4#/sack cello-flake and 5#/sack gilsonite (yield 2.04, weight 12.5). Tailed in with 200 sacks Class C with 2% CaCl2 (yield 1.34, weight 14.8). PD 12:30 PM 7-3-99. Bumped plug to 843 psi, OK. Circulated 161 sacks cement. WOC. Nippled up and tested to 1000# for 15 minutes. Drilled out at 12:30 PM 7-4-99. WOC 24 hours. Reduced hole to 7-7/8". Resumed drilling.

ACCEPTED FOR RECORD

JUL 15 1999

ORIG. SGL. LES. BABYAK
BLM

14. I hereby certify that the foregoing is true and correct

Signed

Title Operations Technician

Date July 8, 1999

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See instruction on Reverse Side

