Form 3160-3 (December 1990)	DEPARTMEN	STATES	SUBMIT IN	811 ARTESIA	CONS. DIVIS S. 1ST ST. , NM-0824002084	olyr		
BUREAU OF LAND MANAGEMENT					5. LEASE DESIGNATION AND SERIAL NO. LC-057798			
AI	PPLICATION FOR PER	MIT TO DRILL OR DE	EPEN	_	6.17 INDIAN, ALLOTTER OR TRIBE NAME			
la TYPE OF WORK: DRILL DEEPEN					NA			
b. TYPE OF WELL:					7. UNIT AGREEMENT NAME			
2 NAME OF OPERATOR DEVON ENERGY CORPORATION (NEVADA) ノノフフ				Logan 3	Logan 35 Federal #13 239/4			
3. ADDRESS AND TELEPHONE NO.				- 9.API WELL NO. 30-015- 3 7 7 5				
		E 1500, OKC, OK 73102 (4	· · · · · · · · · · · · · · · · · · ·	10.FIELD AND POOL, OR WILDCAT				
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)* At surface 990' FSL & 990 FWL, Unit "M" At top proposed prod. zone (SAME) 14. DISTANCE IN MILES AND DIRECTION FROM NEAREST TOWN OF POST OFFICE:				Red Lake; Glor-Yeso, NE and/or San Andres 11.5EC., T., R., M., OR BLOCK AND SURVEY OR AREA Section 35-T17S-27E				
Approximately 7 miles	NO DIRECTION FROM NEAREST TOWN ( southeast of Artesia, NM	19 OF PECE		12. COUN Eddy C	TY OR PARISH OUNTY	13. STATE New Mexico		
15.DISTANCE FROM PROPO LOCATION TO NEAREST PROPERTY OR LEASE L (Also to nearest drig, unit lim		16.NO. OF ACRES IN LEASE	ARTESIA		17.NO. OF ACRES TO THIS WELL 40			
18.DISTANCE FROM PROPO TO NEAREST WELL, DR OR APPLIED FOR, ON	ILLING, COMPLETED,	19. PROPOSED DEPTH 1016	8299750		20. ROTARY OR CAR Rotary	BLE TOOLS*		
21. ELEVATIONS (Show whe GR 3620'	ther DF, RT, GR, etc.)	- I			APPROX. DATE WORK WI tember 15, 1999			
23.		PROPOSED CASING AND C			1	TPI + Loc		
SIZE OF HOLE	GRADE, SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	I	QUANTITY O	CEMENT		
17 1/2"	14"	Conductor	40'		Redimix			
12 1/4"	8 5/8", J-55	24 ppf	1150' WITNESS		350 sx Lite + 200 sx Class C			
7 7/8"	5 1/2", J-55	15.5 ppf	4500'		250 sx Lite + 450 sx Class C			
Devon Energy plans to	lated to surface on all casing strin drill to 4500° +/- to test the Glori commercial, the wellbore will be	eta-Yeso and/or San Andres For						

Chok Exhibit #2 - Locat Exhibit #3 - Plann Exhibit #4 - Wells Exhibit #5 - Produ Exhibit #6 - Rotar Exhibit #7 - Casin Exhibit #8 - H <sub>2</sub> S O IN ABOVE SPAC	out Prevention Equipment/ te Manifold ion and Elevation Plat ed Access Roads Within a One Mile Radius action Facilities Plan y Rig Layout g Design Parameters and Factors Operating Plan E DESCRIBE PROPOSED PROGRAM: If pro	operations o Bond Cove BLM Bond Doposal is to deep	The undersigned accepts all applicable terms, conditions, stipulation, and restrictions concer operations conducted on the leased land or portion thereof, as described above. Bond Coverage: Nationwide BLM Bond File No.: CO-1104 APPROVAL SUBJECT TO GENERAL REQUIREMENTS AND SPECIAL STIPULATIONS CACHED osal is to deepen, give data on present productive zone and proposed new productive zone. If					
<u>any.</u> 24.	E. L, Buthott, h		E. L. BUTTROSS, JR. DISTRICT ENGINEER	DATE	s. Give blowor	ut preventer progra	ım, if	
*(This space for	Federal or State office use)	·		<u></u>	<u></u>			
PERMIT NO.		APPROVAL DATE						
	does not warrant or certify that the applicant holds leg F APPROVAL, IF ANY:	gal or equitable tit Acut	ра – – – – – – – – – – – – – – – – – – –			nt to conduct operation	ns thereon.	
APPROVED BY	(URIG. SGU.) ARMANDU A. LOPEZ	TITLE	Assistant Field Office Lands and Minerals	e manager,	DATE 6	9/24/99		

APPROVED BY	(ÜKIG.	540.1	ARMANDU	A-	LUPEZ	
-------------	--------	-------	---------	----	-------	--

outlined in the following exhibits and attachments.

TITLE \_

E/24 DATE \_

## See Instructions On Reverse Side

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction



. ---

·~ !:

ż

• •

DISTRICT I P.O. Box 1980, Hobbs, NM 88240 EX JIT# 2 State of New Mexico

Energy, Minerais and Natural Resources Department

DISTRICT II P.O. Drawer DD, Artemia, NM 88210

DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87410 Form C-102 Revised February 10, 1994 Instruction on back Submit to Appropriate District Office State Lease - 4 Copies Fee Lease - 3 Copies

BASIN SURVEY S

## OIL CONSERVATION DIVISION

P.O. Box 2088 Santa Fe, New Mexico 87504-2088

□ AMENDED REPORT

## WELL LOCATION AND ACREAGE DEDICATION PLAT API Number Pool Code Pool Name 96836 Red Lake; Glorieta-Yeso, NE **Property** Code Property Name Well Number 23714 LOGAN "35" FEDERAL 13 OGRID No. **Operator** Name Elevation 6137 DEVON ENERGY CORPORATION 3620' Surface Location UL or lot No. Section Township Range Lot Idn Feet from the North/South line Feet from the East/West line County Μ 35 17 S 27 E 990 SOUTH 990 WEST EDDY Bottom Hole Location If Different From Surface UL or lot No. Section Township Range Lot Idn Feet from the North/South line Feet from the East/West line County Dedicated Acres Joint or Infill Consolidation Code Order No. NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION OPERATOR CERTIFICATION I hereby certify the the information contained herein is true and complete to the best of my knowledge and belief. E.I.B. thou, fr. Signature E.L. Buttross, Jr. Printed Name District Engineer Title July 20, 1999 Date SURVEYOR CERTIFICATION I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervison and that the same is true and correct to the best of my belief. 1999 tufe services Date 3618.9 5 3618.9 Sig P essionel 990 3621.3' 3618.2 7977 POFESSION

succes, minerals and natura

EXHIBIT# 1



## Attachment to Exhibit #1 NOTES REGARDING BLOWOUT PREVENTORS Logan 35 Federal #13 Eddy County, New Mexico

- 1. Drilling nipple will be constructed so it can be removed mechanically without the aid of a welder. The minimum internal diameter will equal BOP bore.
- 2. Wear ring will be properly installed in head.
- 3. Blowout preventor and all associated fittings will be in operable condition and tested to 1000 psi with the rig pump.
- 4. All fittings will be flanged.
- 5. A full bore safety valve with proper thread connections will be available on the rotary rig floor at all times.
- 6. All choke lines will be anchored to prevent movement.
- 7. All BOP equipment will be equal to or larger in bore than the internal diameter of the last casing string.
- 8. Will maintain a Kelly cock attached to the Kelly.
- 9. Hand wheels and wrenches will be properly installed and tested for safe operation.
- 10. All BOP equipment will meet API standards and include a minimum 40 gallon accumulator having two independent means of power to initiate closing operation.