Form 3160-5 (June 1990)

## UNTED STATES

## DEPARTME... OF THE INTERIMM. Oil Cons. Jision

BUREAU OF LAND MANAGEMENT S. 1st Street

FORM APPROVED

Budget Bureau No. 1004-0135

SUNDRY NOTICES AND REPORTS ON AFTESIA, NM 88210-2834 Expires March 31, 1993 5. Lease Designation and Serial No. Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. LC-057798 Use "APPLICATION FOR PERMIT—" for such proposals 6. If Indian, Allottee or Tribe Name SUBMIT IN TRIPLICATE 7. If Unit or CA, Agreement Designation 1. Type of Well ⊠ Oil Well ☐ Gas Well Other 8. Well Name and No. 2. Name of Operator **DEVON ENERGY PRODUCTION COMPANY, L.P.** Logan 35 Federal #13 9. API Well No. 3. Address and Telephone No. 20 NORTH BROADWAY, SUITE 1500, OKLAHOMA CITY, OKLAHOMA 30-015-30735 10. Field and Pool, or Exploratory Area 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) Red Lake; Glorieta-Yeso, NE 990' FSL & 990' FWL, Section 35-17S-27E, Unit "M" 11. County or Parish, State Eddy County, NM CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent Abandonment Change of Plans New Construction Recompletion Non-Routine Fracturing Subsequent Report Plugging Back Casing Repair Water Shut-Off Conversion to Injection Final Abandonment Notice Altering Casing Other Spud,csg string,TD Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\* Spud well on 10/12/00 at 1830 hrs and drld an 11" hole to 1150'. On 10/15/00 ran 25 jts 8 5/8" 24# J-55 8RD STC csg, set @ 1141'; cemented w/ 300 sx class "C" + 200 sx 35:65 POZ. 60 sx cmt returned to surface. Drld 77/8" hole and reached TD 3800' on 10/20/00 at 1730 hrs. Schlumberger ran Platform Express Three Detector Litho-Density CNL/GR and Azimuthal Laterolog Micro-CFL/GR. Ran 87 its 5 1/2" 15.5# J-55 LTC 8RD csg, set @ 3795'. Cemented w/ 200 sx 35:65 POZ C + 550 sx 50:50 POZ C. Estimated top of cement 600'. Released rig at 2100 hrs 10/21/00. WOCU. 14. I hereby certify that the foregoing is true and correct Tonja Rutelonis Date 11/7/00 Title Engineering Technician (This space for Federal or State office use) Approved by Conditions of approval, if any: