

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof; cored intervals; and all drill stem, tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries):						38. GEOLOGIC MARKERS	
FORMATION		TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	TOP	
						MEAS. DEPTH	TRUE VERT. DEPTH
Premier sand	1580'	1620'	sandstone		Bowers	362'	
San Andres	1620'	2974'	dolomite		Queen	683'	
Glorieta	2974'	3056'	sd & dolomite		Grayburg	1307'	
Yeso	3056'	3700'	dolomite		Premier	1580'	
			DEPTH	ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.. (continued from the front)	San Andres	1620'	
		3092' - 3290'		32,000 gal FW prepad + 105,000 gal linear gelled wtr + 74,500# 20/40 Brady sand + 15,000# CRC sd	Glorieta	2974'	
		2672' - 2784'		22,000 gals FW, 73,210 Aqua Frac 1000, 1620 FW, 800 gal 15% HCL acid spot 61,680# 20/40 sand + 13,085 16/30 CR 4000 sand	Yeso	3056'	
		1986' - 2324'		1,945 FW Flush, 1,700 15% HCL acid spot, 2,550 gal FW Flush, 30,000 gal FW, 99,000 gal Aqua Frac 1000, 78,640# 20/40 sand + 17,085 CR 4000 18/30 sand			

1911

