Form 3160-5 (August 1999)

Approved by

Conditions of approval, if any, are attached. Approval of this notice does not warrant or

certify that the applicant holds legal or equitable title to those rights in the subject lease

which would entitle the applicant to conduct operations thereon.

ITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

─ Oil Cons.	45/
M. DIV-Dist. 2 ORM APP	ROVED
1301 W. Grand Aventue 1	004-0135 her 30, 2000
Artesia, NM ₅ 882 Qi No.	ioci 50, 2000

SUNDRY NOTICES AND REPORTS ON WELLS LC028375b Do not use this form for proposals to drill or to re-enter an 6. If Indian, Allottee or Tribe Name abandoned well. Use Form 3160-3 (APD) for such proposals. SUBMIT IN TRIPLICATE - Other instructions on reverse side 7. If Unit or CA/Agreement, Name and/or 1. Type of Well Oil Well Gas Well x Other 8. Well Name and No. Dry Hole OXY Jazz Federal 2. Name of Operator OXY USA WIP Limited Partnership 9. API Well No. 3a. Address Phone No. (include area code) 30-015-30748 P.O. Box 50250, Midland, TX 10. Field and Pool, or Exploratory Area 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) Crow Flats Morrow 660 FNL 1980 FWL NEWW(3) Sec 4 T17S R27E 33486 11. County or Parish, State Eddv 12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION X Notice of Intent Acidize Deepen Production (Start/Resume) Water Shut-Off Alter Casing Fracture Treat Reclamation Well Integrity Subsequent Report Casing Repair New Construction Recomplete Other Change Plans Plug and Abandon Temporarily Abandon Final Abandonment Notice Convert to Injection Plug Back Water Disposal Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. 13. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the final site is ready for final inspection.) TD - 9150' PBTD - 9089' PERFS - 8742-8790' CASING:13-3/8" 48# @ 407', 17-1/2", cmt w/363sx, TOC-Circ 8-5/8" 32# @ 1822', 11", cmt w/1015sx, TOC-Circ 5-1/2" 17# @ 9150', 7-7/8", cmt w/860sx, TOC-5168'-CBL RIH & set CIBP @ 8692', dump 5sx cmt on top M&P 25sx cmt @ 8459-8359' M&P 25sx cmt @ 5912-5812' APPROVAL SUBJECT TO 3. Cut & pull 5-1/2" csg at approximately 5150' **GENERAL REQUIREMENTS AND** M&P 30sx cmt @ 5200-5100', WOC-TAG M&P 35sx cmt @ 3400-3300' SPECIAL STIPULATIONS ATTACHED M&P 35sx cmt. @ 1872-1772' 7. M&P 35sx cmt @ 457-357' M&P 20sx cmt Surface Plug 10# MLF BETWEEN PLUGS I hereby certify that the foregoing is true and correct Name (Printed/Typed) Title David Stewart Sr. Regulatory Analyst Date 02 THIS SPACE FOR FEDERAL OR STATE OFFICE USE (ORIG. SGD.) ALEXIS C. SWOBODA Title ETROLEUM ENGINEER

Title 18 U.S.C. Section 1001, and Title 43 U.S.C. Section 1212, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

Office

OXY USA WTP LP OXY JAZZ FEDERAL #1 SEC 4 T17 R27E EDDY NM

0.0 - 60.0' CEMENT PLUG 20sx

357.0 - 457.0' CEMENT PLUG 35sx

1772.0 - 1872.0' CEMENT PLUG 35sx

3300.0 - 3400.0' CEMENT PLUG 35sx

5100.0 - 5200.0' CEMENT PLUG 30sx

5812.0 - 5912.0' CEMENT PLUG 25sx

8359.0 - 8459.0' CEMENT PLUG 25sx 8657.0 - 8692.0' CEMENT PLUG 5sx 8692.0 - 8692.0' CIBP 0.0 - 407.0' 17-1/2" OD HOLE 0.0 - 407.0' CEMENT 363sx-CIRC 0.0 - 407.0' 13-3/8" OD SURF CSG

407.0 - 1822.0' 11" OD HOLE 0.0 - 1822.0' CEMENT 1015sx-CIRC 0.0 - 1822.0' 8-5/8" OD INT CSG

1822.0 - 9150.0' 7-7/8" OD HOLE 5168.0 - 9150.0' CEMENT 860sx-CBL 5150.0 - 9150.0' 5-1/2" OD PROD CSG

8742.0 - 8790.0' ABANDONED PERFS

TD: 9150'