

GENERAL DRILLING PROGRAM- Attachment to Form C-101

Southwestern Energy Production Company- No Bluff State Com. #1
660' FNL 1350' FWL Section 36-T17S-R27E
Eddy County, New Mexico

Elevation: 3603' GR

Proposed Total Depth: 10,150'

Estimated Formation Tops

San Andres	1851'
Glorietta	3355'
Wolfcamp	6670'
Strawn	9030'
Morrow Clastics	9770'
Missippian	10,070'

Casing/Cement Program

<u>Hole Size</u>	<u>Casing Size/Weight/Grade</u>	<u>Setting Depth</u>	<u>Cement</u>	<u>Est. TOC</u>
	20" Conductor pipe	40'	ready mix	surface
17-1/2"	13-3/8" 61# J-55 ST&C	425'	1500 sx 15:85 Poz: Class C + 0.25 pps D29+2% S1+2% D20	surface
12-1/4"	8-5/8" 32# J-55 ST&C	2000'	Lead: 1260 sx 35:65 Poz: Class C + 6% D20+ 0.25 pps D29 Tail: 235 sx Class C+ 2% S1 +0.25 pps D29	surface
7-7/8"	5-1/2" 17# N-80 LT&C	10,150'	860 sx 50:50 Poz: Class H + 6% D44 +2% D20+0.4% D59	8000'

Drilling Fluids Program

<u>Depth</u>	<u>Mud Weight</u>	<u>Viscosity</u>	<u>Fluid Loss</u>	<u>Comments</u>
0-425'	8.4-8.6	32-34	NC	spud mud
425'-2000'	9.0-9.2	28-29	NC	cut brine water,paper,caustic
2000'-9300'	8.4-9.3	28-29	NC	cut brine,caustic,paper
9300'-10,150'	9.3-9.6	34-38	<15 cc	xanthan gum, starch

Blowout Prevention Program- Attachment to Form C-101

0'-425'	None
425'-2000'	20" 2000# annular preventer system.