

Submit 3 Copies To Appropriate District
Office

District I

1625 N. French Dr., Hobbs, NM 88240

District II

811 South First, Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION

2040 South Pacheco
Santa Fe, NM 87505

Form C-103

Revised March 25, 1999

WELL API NO. 30-015-30907

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

V5512

7. Lease Name or Unit Agreement
Name:

No Bluff State Com.

8. Well No. 1

8. Pool name or Wildcat Illinois Camp
Chalk Bluff (Morrow), North

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☒ Other

2. Name of Operator

Southwestern Energy Production Company

3. Address of Operator

2350 N. Sam Houston Parkway East, Suite 300 - Houston, TX 77032

4. Well Location

Unit Letter D : 860 feet from the W line and 660 feet from the N line

Section 36 Township 17S Range 27E NMPM Eddy County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

3589 GR

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

1/19/00 Spud @ 12:00 noon. Drill and survey to 445'.

1/20/00 Set 10 jts 13 3/8", J-55, 61#, ST&C casing to 445' (Total pipe - 450.09') Cement with lead of 150 sx RFC (13-3-A) + 5 pps D-42 + 0.5 pps D-29 (density 14.2 ppg) yield 1.6 ft/sk. Tail w/400 sx 15/85 POZ C plus 2% D-20 plus 0.25 pps D-29. Density 13.8 ppg, yield 1.56 ft/sk. Plug down @ 9:10 am. Circ 72829.5 cm to reserve. WOC 18 hrs. Tst to 500 psi. OK



I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Cathy Rowan

TITLE Drilling Technician

DATE

03/24/00

Type or print name Cathy Rowan

Telephone No. 281-618-4733

(This space for State use)

APPROVED BY Jim W. Gurn

TITLE District Supervisor

DATE

MAY 10 2000

Conditions of approval, if any: